



320150558 P

**BAE SAMLESBURY
LOGISTICS FACILITY**

**SURFACE WATER DRAINAGE
DESIGN**

**6751
REVISION S1**

**Prepared for
AEW Architects**

JUNE 2015

TRP Consulting
The Landmark
21 Back Turner Street
Manchester
M4 1FR

Tel 0161 839 9113
E-mail manchester@trpconsult.com

General Principles


The Logistics Facility to be constructed on the Samlesbury Enterprise Zone, formerly part of the BAE Systems site at Samlesbury. The building is a single storey steel framed warehouse of approximately 130,000 sq.ft incorporating a small single storey internal office and a first floor mezzanine storage area. In addition to the main warehouse building there are associated roads, service areas, car parks and landscaped mounding.

The total Logistics development site area is approximately 4.56 hectares. The impermeable area associated with the first phase development is approximately 2.37 hectares.

Environment Agency Flood Mapping indicates that the site is located in Flood Zone 1 (low probability of flooding). Flood Zone 1 land has been assessed as having 0.1% (1 in 1000 year) chance of flooding from rivers or the sea in any given year.


The Samlesbury site was formerly a World War 2 airfield which was subsequently developed for aircraft component manufacture and assembly.

Prior to construction of the airfield in the late 1930's the site was formerly undeveloped open farmland. An extract from historic mapping with the site outlined in red is shown below.



Site layout superimposed on OS Survey plan 1892

The site is currently largely open grass land with earth mounding along the southern and western boundaries. The existing former runways lie beyond the site boundary to the south and west.



Site layout superimposed on OS Survey plan 1992

The site area is served by a land drainage system dating back to construction of the wartime airfield.



Existing drainage superimposed on proposed site layout

A number of existing surface water drains cross the development site picking up run off from the runway and land drainage generally.

A pair of 150mm diameter surface water sewers cross the south west corner of the site. These sewers run across the BAE site and discharge to Huntley Brook to the west of the site. These sewers are to be diverted around the southern boundary of the development site connecting back to the existing on the western boundary.

A 450mm diameter sewer crosses the central area of the development site which then continues across the BAE site to discharge into Mellor Brook to the North West. This sewer is to be diverted around the northern boundary of the development site to connect back into the existing just beyond the western boundary.

A ground investigation comprising of 5Nr shell and auger boreholes and 8Nr trial pits was undertaken on site by Sub Surface North West in June 2015. The investigation confirmed that ground conditions on the site generally comprised 200-300mm of topsoil overlying natural clay strata extending to depths of at least 15 metres.

Soakaway tests were undertaken in the natural cohesive strata. Water was added to the pits from a bowser and water levels were subsequently monitored over a period of 330 to 375 minutes. The soil infiltration rate was unable to be determined in either test due to the relative impermeability of the test strata in both trial pits and the influx of perched groundwater. Copies of trial pit logs and soakaway test results are included in appendix B

The nature of the natural clay soils on the site is such that infiltration drainage systems are unlikely to be effective or practical.

It is therefore proposed that surface water drainage from the site should discharge to the existing surface water network with flows limited to the equivalent green field run off.

QBAR has been calculated using the IH124 method based on a site area of 50 hectares giving an equivalent run off of 6.6 litres/second/hectare. Preliminary design of the surface water drainage systems has been based on a permissible discharge of 5.5 litres/second/hectare. A copy of the calculation for QBAR is included in Appendix A.

The site areas are summarised as follows:

Location	Area	Permissible discharge
Main building roof	1.16	
Service Yard	0.50	
Fire access road	0.16	
Roads	0.15	
Car Parks	0.40	
Total Phase 1 area	2.37 Hectares	13.04 l/s

The total impremable site area equates to 2.37 hectares giving a maximum permitted discharge to the existing surface water sewers of 13.04 l/s

The design should where possible adopt the principles of SUDS as set out in CIRIA Best Practice Manual C523 and Design Manual C522, and as summarised in PPS25.

Run off from external paved areas, car parks and service yard slabs initially discharge to a series of dry swale features, with a total length of approximately 200 metres, to provide a SUDS element to the scheme. The dry swales will provide a degree of retention in the system but it is not anticipated that there will be any significant infiltration. Further storage, in the form of below ground cellular tanks will be incorporated in design of the surface water drainage system and flows attenuated by use of a hydorake in the final manhole.

All discharge from car park areas should be passed through a class 1 bypass interceptor prior to discharge to surface water sewers.

The surface water drainage system is split into two networks to cover the eastern and western halves of the site. The western network discharges to the diverted 450mm diameter sewer which ultimately discharges to Mellor Brook. The eastern network discharges to the diverted 150mm diameter sewer which ultimately discharges to Huntley Brook.

The following criteria should be adopted for design of the surface water drainage system.

- The drainage network is to be designed as a gravity system to accommodate run off from a 1 in 2 year storm event with no surcharge.
- The network is to be checked for a 1 in 30 year storm event with surcharge permitted but with no surface flooding
- The network is to be checked for a 1 in 100 year storm event with surface flooding permitted providing that there is no risk of flooding to buildings and there is no off site overland flow.
- An allowance to be made for a 30% increase in peak rainfall intensity to account for climate change.
- The discharge from the system will be limited to the peak rural run off rate of 5.5 l/sec/hectare.

Flow from the site will be restricted to 13.04 litres/second by use of a hydrobrake in the final manhole. The design of the surface water drainage system incorporates approximately 200 linear metres of dry swale and 1600-1800m³ of cellular storage located in the car park to the east of the building.

Copies of Micro Drainage simulation output is included in appendix C for reference

All car park drainage will pass through a Class 1 by pass separator prior to discharge to the site sewers.

The surface water drainage system and attenuation has been designed to accept run off from the first phase of the Logistics Facility development. It has been assumed that the Logistics Centre extension and additional car parking will be provided with its own attenuation in the form of below ground cellular storage located at the southern end of the site.

APPENDIX A

GREEN FIELD RUN OFF QBAR

**BAE SAMLESBURY - LOGISTICS FACILITY
SURFACE WATER DRAINAGE PROPOSALS**



TRP Consulting		Page 1
The Landmark 21 Back Turner Street Manchester		
Date 20/01/2015 08:14	Designed by timr	
File QBAR.SRCX	Checked by	
Micro Drainage	Source Control 2014.1	

IH 124 Mean Annual Flood

Input

Return Period (years) 2 SAAR (mm) 1600 Urban 0.000
Area (ha) 50.000 Soil 0.450 Region Number Region 10

Results 1/s

QBAR Rural	333.4
QBAR Urban	333.4
Q2 years	310.5
Q1 year	290.1
Q2 years	310.5
Q5 years	396.8
Q10 years	480.1
Q20 years	524.2
Q25 years	546.8
Q30 years	563.8
Q50 years	616.8
Q100 years	693.5
Q200 years	736.8
Q250 years	816.9
Q1000 years	1013.6

APPENDIX B

SOAK AWAY TEST RESULTS AND TRIAL HOLE LOGS

Notes

1. TRP - Authorised Borehole Contractor and Sub-contractors.
 2. Number 4 stringing and restringing to TRP Contracting plan to commencement.
 3. Copy route from site plans, all communications and locate plan prior to commencement.
 4. All boreholes must be numbered sequentially starting from 1 and numbered sequentially.
 5. Work items listed above.
- At time of trial pit or borehole commencement the route to be followed will be agreed by the contractor and the relevant authority.
- Specification issued by TRP Contracting, Subject to Standard Conditions of Project, Consultancy requirements and this Contract Document.

Boreholes S.O.P.s	
DESCRIPTION	Project X
BH100	431354.00
BH101	431354.00
BH102	431354.00
BH103	431354.00
BH104	431354.00
BH105	431354.00
TP01	431354.00
TP02	431354.00
TP03	431354.00
TP04	431354.00
TP05	431354.00
TP06	431354.00
TP07	431354.00
TP08	431354.00
TP09	431354.00
TP10	431354.00
TP11	431354.00
TP12	431354.00
TP13	431354.00
TP14	431354.00
TP15	431354.00
TP16	431354.00
TP17	431354.00
TP18	431354.00
TP19	431354.00
TP20	431354.00
TP21	431354.00
TP22	431354.00
TP23	431354.00
TP24	431354.00
TP25	431354.00
TP26	431354.00
TP27	431354.00
TP28	431354.00
TP29	431354.00
TP30	431354.00
TP31	431354.00
TP32	431354.00
TP33	431354.00
TP34	431354.00
TP35	431354.00
TP36	431354.00
TP37	431354.00
TP38	431354.00
TP39	431354.00
TP40	431354.00
TP41	431354.00
TP42	431354.00
TP43	431354.00
TP44	431354.00
TP45	431354.00
TP46	431354.00
TP47	431354.00
TP48	431354.00
TP49	431354.00
TP50	431354.00
TP51	431354.00
TP52	431354.00
TP53	431354.00
TP54	431354.00
TP55	431354.00
TP56	431354.00
TP57	431354.00
TP58	431354.00
TP59	431354.00
TP60	431354.00
TP61	431354.00
TP62	431354.00
TP63	431354.00
TP64	431354.00
TP65	431354.00
TP66	431354.00
TP67	431354.00
TP68	431354.00
TP69	431354.00
TP70	431354.00
TP71	431354.00
TP72	431354.00
TP73	431354.00
TP74	431354.00
TP75	431354.00
TP76	431354.00
TP77	431354.00
TP78	431354.00
TP79	431354.00
TP80	431354.00
TP81	431354.00
TP82	431354.00
TP83	431354.00
TP84	431354.00
TP85	431354.00
TP86	431354.00
TP87	431354.00
TP88	431354.00
TP89	431354.00
TP90	431354.00
TP91	431354.00
TP92	431354.00
TP93	431354.00
TP94	431354.00
TP95	431354.00
TP96	431354.00
TP97	431354.00
TP98	431354.00
TP99	431354.00
TP100	431354.00
TP101	431354.00
TP102	431354.00
TP103	431354.00
TP104	431354.00
TP105	431354.00
TP106	431354.00
TP107	431354.00
TP108	431354.00
TP109	431354.00
TP110	431354.00
TP111	431354.00
TP112	431354.00
TP113	431354.00
TP114	431354.00
TP115	431354.00
TP116	431354.00
TP117	431354.00
TP118	431354.00
TP119	431354.00
TP120	431354.00
TP121	431354.00
TP122	431354.00
TP123	431354.00
TP124	431354.00
TP125	431354.00
TP126	431354.00
TP127	431354.00
TP128	431354.00
TP129	431354.00
TP130	431354.00
TP131	431354.00
TP132	431354.00
TP133	431354.00
TP134	431354.00
TP135	431354.00
TP136	431354.00
TP137	431354.00
TP138	431354.00
TP139	431354.00
TP140	431354.00
TP141	431354.00
TP142	431354.00
TP143	431354.00
TP144	431354.00
TP145	431354.00
TP146	431354.00
TP147	431354.00
TP148	431354.00
TP149	431354.00
TP150	431354.00
TP151	431354.00
TP152	431354.00
TP153	431354.00
TP154	431354.00
TP155	431354.00
TP156	431354.00
TP157	431354.00
TP158	431354.00
TP159	431354.00
TP160	431354.00
TP161	431354.00
TP162	431354.00
TP163	431354.00
TP164	431354.00
TP165	431354.00
TP166	431354.00
TP167	431354.00
TP168	431354.00
TP169	431354.00
TP170	431354.00
TP171	431354.00
TP172	431354.00
TP173	431354.00
TP174	431354.00
TP175	431354.00
TP176	431354.00
TP177	431354.00
TP178	431354.00
TP179	431354.00
TP180	431354.00
TP181	431354.00
TP182	431354.00
TP183	431354.00
TP184	431354.00
TP185	431354.00
TP186	431354.00
TP187	431354.00
TP188	431354.00
TP189	431354.00
TP190	431354.00
TP191	431354.00
TP192	431354.00
TP193	431354.00
TP194	431354.00
TP195	431354.00
TP196	431354.00
TP197	431354.00
TP198	431354.00
TP199	431354.00
TP200	431354.00
TP201	431354.00
TP202	431354.00
TP203	431354.00
TP204	431354.00
TP205	431354.00
TP206	431354.00
TP207	431354.00
TP208	431354.00
TP209	431354.00
TP210	431354.00
TP211	431354.00
TP212	431354.00
TP213	431354.00
TP214	431354.00
TP215	431354.00
TP216	431354.00
TP217	431354.00
TP218	431354.00
TP219	431354.00
TP220	431354.00
TP221	431354.00
TP222	431354.00
TP223	431354.00
TP224	431354.00
TP225	431354.00
TP226	431354.00
TP227	431354.00
TP228	431354.00
TP229	431354.00
TP230	431354.00
TP231	431354.00
TP232	431354.00
TP233	431354.00
TP234	431354.00
TP235	431354.00
TP236	431354.00
TP237	431354.00
TP238	431354.00
TP239	431354.00
TP240	431354.00
TP241	431354.00
TP242	431354.00
TP243	431354.00
TP244	431354.00
TP245	431354.00
TP246	431354.00
TP247	431354.00
TP248	431354.00
TP249	431354.00
TP250	431354.00
TP251	431354.00
TP252	431354.00
TP253	431354.00
TP254	431354.00
TP255	431354.00
TP256	431354.00
TP257	431354.00
TP258	431354.00
TP259	431354.00
TP260	431354.00
TP261	431354.00
TP262	431354.00
TP263	431354.00
TP264	431354.00
TP265	431354.00
TP266	431354.00
TP267	431354.00
TP268	431354.00
TP269	431354.00
TP270	431354.00
TP271	431354.00
TP272	431354.00
TP273	431354.00
TP274	431354.00
TP275	431354.00
TP276	431354.00
TP277	431354.00
TP278	431354.00
TP279	431354.00
TP280	431354.00
TP281	431354.00
TP282	431354.00
TP283	431354.00
TP284	431354.00
TP285	431354.00
TP286	431354.00
TP287	431354.00
TP288	431354.00
TP289	431354.00
TP290	431354.00
TP291	431354.00
TP292	431354.00
TP293	431354.00
TP294	431354.00
TP295	431354.00
TP296	431354.00
TP297	431354.00
TP298	431354.00
TP299	431354.00
TP300	431354.00
TP301	431354.00
TP302	431354.00
TP303	431354.00
TP304	431354.00
TP305	431354.00
TP306	431354.00
TP307	431354.00
TP308	431354.00
TP309	431354.00
TP310	431354.00
TP311	431354.00
TP312	431354.00
TP313	431354.00
TP314	431354.00
TP315	431354.00
TP316	431354.00
TP317	431354.00
TP318	431354.00
TP319	431354.00
TP320	431354.00
TP321	431354.00
TP322	431354.00
TP323	431354.00
TP324	431354.00
TP325	431354.00
TP326	431354.00
TP327	431354.00
TP328	431354.00
TP329	431354.00
TP330	431354.00
TP331	431354.00
TP332	431354.00
TP333	431354.00
TP334	431354.00
TP335	431354.00
TP336	431354.00
TP337	431354.00
TP338	431354.00
TP339	431354.00
TP340	431354.00
TP341	431354.00
TP342	431354.00
TP343	431354.00
TP344	431354.00
TP345	431354.00
TP346	431354.00
TP347	431354.00
TP348	431354.00
TP349	431354.00
TP350	431354.00
TP351	431354.00
TP352	431354.00
TP353	431354.00
TP354	431354.00
TP355	431354.00
TP356	431354.00
TP357	431354.00
TP358	431354.00
TP359	431354.00
TP360	431354.00
TP361	431354.00
TP362	431354.00
TP363	431354.00
TP364	431354.00
TP365	431354.00
TP366	431354.00
TP367	431354.00
TP368	431354.00
TP369	431354.00
TP370	431354.00
TP371	431354.00
TP372	431354.00
TP373	431354.00
TP374	431354.00
TP375	431354.00
TP376	431354.00
TP377	431354.00
TP378	431354.00
TP379	431354.00
TP380	431354.00
TP381	431354.00
TP382	431354.00
TP383	431354.00
TP384	431354.00
TP385	431354.00
TP386	431354.00
TP387	431354.00
TP388	431354.00
TP389	431354.00
TP390	431354.00
TP391	431354.00
TP392	431354.00
TP393	431354.



SUB SURFACE

SITE INVESTIGATION AND SPECIALIST GEOTECHNICAL CONSULTANTS
3 Peel Street, Preston, PR2 2OS. Tel. (01772) 561135 Fax (01772) 204907


In situ Test Results

Site: LOGISTICS SITE, BAE SAMLESBURY, BALDERSTONE, LANCASHIRE
Client: AEW ARCHITECTS AND DESIGNERS LIMITED
Engineer: TRP CONSULTING

Job Number: 6019
Sheet: 1 / 1

Soakaway Test

Hole No: TP5

TEST NO: 1
DATE: 07/04/15

Time (min)	Depth (m)
0	0.83
0.5	0.83
1	0.83
2	0.83
3	0.83
4	0.83
5	0.83
7	0.82
10	0.82
15	0.82
20	0.82
30	0.82
45	0.82
60	0.82
75	0.82
90	0.82
105	0.82
120	0.82
135	0.82
150	0.82
165	0.82
180	0.82
195	0.82
210	0.82
225	0.82
240	0.82
255	0.82
270	0.82
285	0.82
300	0.82
315	0.82
330	0.82

Length of pit: L = 1.50 m

Width of pit: W = 0.47 m

Depth of pit D = 1.80 m

Base area of pit: A = 0.71 m²

100% effective depth D100 = 0.83 m

75% effective depth D75 = 1.07 m

50% effective depth D50 = 1.32 m

25% effective depth D25 = 1.56 m

time to D75 T75 = — sec

time to D25 T25 = — sec

time from D75 to D25 t_{D75-D25} = — sec
(T25 - T75)volume between D75 & D25 V_{D75-D25} = 0.34 m³
(A x (D25 - D75))surface area to D50 inc. base a_{D50} = 2.62 m²
(2x(D-D50)x(W+L)) + A)SOIL INFILTRATION RATE f = $\frac{V_{D75-D25}}{a_{D50} \times t_{D75-D25}}$

f = N/A* m/sec

Test Strata:
(see Trial Pit)

Remarks: *Unable to determine soil infiltration rate due to relative impermeability of tests strata.



SUB SURFACE

SITE INVESTIGATION AND SPECIALIST GEOTECHNICAL CONSULTANTS
3 Peel Street, Preston, PR2 2QS. Tel. (01772) 561135 Fax (01772) 204907

In situ Test Results

Site: LOGISTICS SITE, BAE SAMLESBURY, BALDERSTONE, LANCASHIRE
Client: AEW ARCHITECTS AND DESIGNERS LIMITED
Engineer: TRP CONSULTING


Job Number
6019
Sheet
1 / 1

Soakaway Test

Hole No: TP7

TEST NO: 1
DATE: 07/04/15

Time (mins)



Time (min)	Depth (m)
0	0.61
0.5	0.61
1	0.61
2	0.61
3	0.61
4	0.61
5	0.61
7	0.61
10	0.60
15	0.60
20	0.60
30	0.60
45	0.59
60	0.59
75	0.59
90	0.59
105	0.59
120	0.59
135	0.59
150	0.56
165	0.56
180	0.56
195	0.56
210	0.54
225	0.54
240	0.54
255	0.54
270	0.54
285	0.54
375	0.52

Length of pit: L = 1.20 m
 Width of pit: W = 0.47 m
 Depth of pit D = 1.80 m
 Base area of pit: A = 0.56 m²

100% effective depth D100 = 0.61 m
 75% effective depth D75 = 0.91 m
 50% effective depth D50 = 1.21 m
 25% effective depth D25 = 1.50 m

time to D75 T75 = — sec
 time to D25 T25 = — sec

time from D75 to D25 t_{p75-25} = — sec
 (T25 - T75)

volume between D75 & D25 V_{p75-25} = 0.34 m³
 (A x (D25 - D75))

surface area to D50 inc. base a_{p50} = 2.55 m²
 ((2x(D-D50)x(W+L)) + A)

SOIL INFILTRATION RATE f = $\frac{V_{p75-25}}{a_{p50} \times t_{p75-25}}$

f = N/A* m/sec

Test Strata:
(see Trial Pit)

Remarks: *Unable to determine soil infiltration rate due to influx of groundwater



SUB SURFACE

SITE INVESTIGATION, GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS
3 Peel Street, Preston, PR2 2QS. Tel. (01772) 561135 Fax (01772) 204907

Site						Trial Pit Number
LOGISTICS SITE, BAE SAMLESBURY, LANCASHIRE						TP5
Excavation Method		Dimensions	Ground Level (mOD)	Client		Job Number
MECHANICAL EXCAVATOR		0.47m x 1.50m		AEW ARCHITECTS & DESIGNERS LTD		6019
Location		AS PLAN	Dates	Engineer		Sheet
			07/04/2015	TRP CONSULTING LTD		1/1
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description
0.10-0.30	A				(0.40)	MADE GROUND: long grasses over dark grey and dark brown and brown mottled slightly sandy slightly gravelly clay (topsoil) with many roots and rootlets. Gravel sized fragments are fine to coarse stone and occasional brick.
0.10-0.30	B				0.40	
0.10-0.30	D				(0.50)	
0.10-0.30	V					
0.40-0.60	B					
0.60-0.80	B	HV@0.60m, c=97kPa			(0.50)	Stiff high strength brown, orange brown, light grey, red brown, greenish brown and yellow brown mottled sandy gravelly CLAY with low cobble content of quartz and with some rootlets and lenses of silty fine to medium sand. Gravel is subangular fine to coarse quartz, sandstone and siltstone.
0.90	D	HV@0.90m, c=102kPa			0.90	Stiff high strength brown and light grey mottled slightly sandy slightly gravelly CLAY with some root remains and lenses of fine to coarse sand and fine gravel. Gravel is subangular to rounded fine to coarse quartz, sandstone and siltstone.
		HV@1.20m, c=100kPa			(0.90)	
		HV@1.50m, c=130+kPa			 below 1.60m : with some plant remains
1.80	D	07/04/2015:DRY			1.80	Complete at 1.80m
Plan						Remarks
						Pit sides remained stable and vertical. No groundwater encountered. A = Amber glass jar sample V = Vial sample HV = Hand Shear Vane test On completion a soakaway test was carried out before being backfilled with arisings.
						Scale (approx)
						Logged By
						Figure No.
						1:25
						ALWSJ
						6019.TP5



SUB SURFACE

SITE INVESTIGATION, GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS
3 Peel Street, Preston, PR2 2QS. Tel. (01772) 551135 Fax (01772) 204907

Site

**Trial Pit
Number**
TP7

Excavation Method MECHANICAL EXCAVATOR		Dimensions 0.47m x 1.20m		Ground Level (mOD)		Client AEW ARCHITECTS & DESIGNERS LTD		Job Number 6019
		Location AS PLAN		Dates 07/04/2015		Engineer TRP CONSULTING LTD		Sheet 1/1
Depth (m)	Sample / Tests	Water Depth (m)	Field Records	Level (mOD)	Depth (m) (Thickness)	Description		Legend
0.05-0.15	A				(0.15)	MADE GROUND: grass over dark grey brown slightly sandy slightly gravelly clay (topsoil) with many rootlets. Gravel sized fragments are fine to coarse stone and occasional brick.		
0.05-0.15	D				0.15			
0.05-0.15	V							
0.30-0.50	A				(0.55)	MADE GROUND: dark grey, dark grey brown and brown slightly sandy slightly gravelly clay with some plant and root remains and some rootlets. Gravel sized fragments are fine to coarse stone and occasional brick.		
0.30-0.50	D							
0.50-0.50	V							
			HV@0.70m, c=93kPa		0.70			
0.80	D				(0.40)	Stiff high strength brown, light brown, light grey and greenish brown slightly sandy slightly gravelly CLAY with occasional rootlets and lenses of silty fine to medium sand. Gravel is subangular to subrounded fine to coarse quartz, sandstone and siltstone.		
1.20	D		HV@1.20m, c=91kPa		1.10	Stiff high strength brown and grey mottled slightly sandy slightly gravelly CLAY with occasional rootlets, plant and root remains. Gravel is subangular to rounded fine to coarse quartz		
					(0.70)			
			HV@1.60m, c=125kPa		1.80			
1.80	D		07/04/2015,DRY			Complete at 1.80m		
Plan					Remarks			
					Pit sides remained stable and vertical. Slight seepage at base. A = Amber glass jar sample V = Vial sample HV = Hand Shear Vane test On completion a soakaway test was carried out before being backfilled with arisings.			
</								

APPENDIX C

MICRO DRAINAGE SIMULATION OUTPUT

APPENDIX C1

MICRO DRAINAGE SIMULATION OUTPUT – Western site network

The Landmark
21 Back Turner Street
Manchester

Date 23/06/2015 09:28
File 6751 Logistics drainage
Micro Drainage

Designed by timx

Checked by

Network 2014.1

STORM SEWER DESIGN by the Modified Rational MethodDesign Criteria for West StormPipe Sizes STANDARD Manhole Sizes STANDARDFSR Rainfall Model - England and Wales

Return Period (years)	100	Add Flow / Climate Change (%)	30
M5-60 (mm)	18.900	Minimum Backdrop Height (m)	0.200
Ratio R	0.300	Maximum Backdrop Height (m)	1.500
Maximum Rainfall (mm/hr)	75	Min Design Depth for Optimisation (m)	0.900
Maximum Time of Concentration (mins)	30	Min Vel for Auto Design only (m/s)	1.00
Foul Sewage (l/s/ha)	0.000	Min Slope for Optimisation (1:X)	250
Volumetric Runoff Coeff.	0.750		

Designed with Level Soffits

Network Design Table for West Storm

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Auto Design
SW1.000	8.120	0.057	142.5	0.164	5.00	0.0	0.600	o	300	g
SW1.001	37.488	0.193	194.2	0.000	0.00	0.0	0.600	o	300	g
SW2.000	6.072	0.175	34.7	0.268	5.00	0.0	0.600	c	225	g
SW1.002	41.120	0.164	250.0	0.000	0.00	0.0	0.600	c	375	g
SW3.000	6.173	0.339	16.2	0.154	5.00	0.0	0.600	o	150	g
SW1.003	48.703	0.262	186.0	0.000	0.00	0.0	0.600	o	450	g
SW4.000	42.110	0.175	241.2	0.264	5.00	0.0	0.600	o	300	g
SW4.001	106.697	0.427	250.0	0.161	0.00	0.0	0.600	c	375	g

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
SW1.000	75.00	5.10	76.225	0.164	0.0	0.0	10.0	1.32	93.0	43.2
SW1.001	75.00	5.66	76.168	0.164	0.0	0.0	10.0	1.12	78.5	43.2
SW2.000	75.00	5.05	76.225	0.268	0.0	0.0	16.3	2.23	88.6	70.8
SW1.002	75.00	6.26	75.900	0.432	0.0	0.0	26.3	1.14	126.1	114.1
SW3.000	75.00	5.04	76.300	0.154	0.0	0.0	9.4	2.37	41.9	40.6
SW1.003	75.00	6.80	75.661	0.586	0.0	0.0	35.7	1.49	236.6	154.6
SW4.000	75.00	5.70	76.150	0.264	0.0	0.0	16.1	1.01	71.2	69.8
SW4.001	75.00	7.25	75.900	0.425	0.0	0.0	25.9	1.14	126.1	112.2

TRP Consulting		Page 2
The Landmark 21 Back Turner Street Manchester		
Date 23/06/2015 09:28	Designed by timr	
File 6751 Logistics drainage	Checked by	
Micro Drainage	Network 2014.1	

Network Design Table for West Storm

PN	Length (m)	Fall (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k SECT	HYD (mm)	DIA (mm)	Auto Design
SW1.004	6.263	0.025	250.0	0.000	0.00	o	0.600	525	
SW1.005	47.982	0.192	250.0	0.000	0.00	o	0.600	525	
SW1.006	3.080	0.012	250.0	0.000	0.00	o	0.600	525	

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul Flow (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
SW1.004	75.00	7.33	75.324	1.011	0.0	0.0	61.6	1.41	305.7	266.9
SW1.005	75.00	7.89	75.299	1.011	0.0	0.0	61.6	1.41	305.7	266.9
SW1.006	75.00	5.04	75.107	0.000	5.6	0.0	1.3	1.41	305.7	5.6

The Landmark
21 Back Turner Street
Manchester

Date 23/06/2015 09:28
File 6751 Logistics drainage

Micro Drainage

Designed by timr

Checked by

Network 2014.1

Manhole Schedules for West Storm

MH Name	MH CL (m)	MH Depth (m)	MH Connection	MH Diam., L*W (mm)	PN	Pipe Out Invert Level (m)	Diameter (mm)	PN	Pipes In Invert Level (m)	Diameter (mm)	Backdrop (mm)
SW1	77.350	1.125	Open Manhole	1200	SW1.000	76.225	300				
SW2	77.300	1.132	Open Manhole	1200	SW1.001	76.168	300	SW1.000	76.168	300	
SW3	77.350	1.125	Open Manhole	1200	SW2.000	76.225	225				
SW4	77.175	1.275	Open Manhole	1350	SW1.002	75.900	375	SW1.001	75.975	300	
								SW2.000	76.050	225	
SW5	77.350	1.050	Open Manhole	1200	SW3.000	76.300	150				
SW6	77.175	1.514	Open Manhole	1350	SW1.003	75.661	450	SW1.002	75.736	375	
								SW3.000	75.961	150	
SW7	77.350	1.200	Open Manhole	1200	SW4.000	76.150	300				
SW8	77.350	1.450	Open Manhole	1350	SW4.001	75.900	375	SW4.000	75.975	300	
SW9	77.350	2.026	Open Manhole	1500	SW1.004	75.324	525	SW1.003	75.399	450	
								SW4.001	75.474	375	
SW10	77.000	1.701	Open Manhole	1500	SW1.005	75.299	525	SW1.004	75.299	525	
SW11	77.000	1.893	Open Manhole	1500	SW1.006	75.107	525	SW1.005	75.107	525	
SW	76.000	0.906	Open Manhole	0		OUTFALL		SW1.006	75.094	525	

Free Flowing Outfall Details for West Storm

Outfall Pipe Number	Outfall Name	C. Level (m)	I. Level (m)	Min I. Level (mm)	D,L (mm)	W (m)
SW1.006	SW	76.000	75.094	73.000	0	0

Simulation Criteria for West Storm

Volumetric Runoff Coeff	0.750	Additional Flow - % of Total Flow	0.000
Areal Reduction Factor	1.000	MADD Factor * 10m³/ha	Storage 2.000
Hot Start (mins)	0	Inlet Coeffiecient	0.800
Hot Start Level (mm)	0	Flow per Person per Day (1/per/day)	0.000
Manhole Headloss Coefn (Global)	0.500	Run Time (mins)	60
Foul Sewage per hectare (l/s)	0.000	Output Interval (mins)	1

Number of Input Hydrographs 0 Number of Offline Controls 0 Number of Time/Area Diagrams 0
Number of Online Controls 1 Number of Storage Structures 1 Number of Real Time Controls 0

Synthetic Rainfall Details

Rainfall Model	FSR	Profile Type	Summer
Return Period (years)	100	Cv (Summer)	0.750
Region England and Wales		Cv (Winter)	0.840
M5-60 (mm)	18.900	Storm Duration (mins)	30
Ratio R	0.300		

TRP Consulting		Page 4
The Landmark 21 Back Turner Street Manchester		
Date 23/06/2015 09:28	Designed by timr	
File 6751 Logistics drainage	Checked by	
Micro Drainage	Network 2014.1	

Online Controls for West Storm

Hydro-Brake Optimum® Manhole: SW11, DS/PN: SW1.006, Volume (m³): 13.4

Unit Reference	MD-SHE-0104-5600-1500-5600
Design Head (m)	1.500
Design Flow (l/s)	5.6
Flush-Flo™	Calculated
Objective	Minimise upstream storage
Diameter (mm)	104
Invert Level (m)	75.107
Minimum Outlet Pipe Diameter (mm)	150
Suggested Manhole Diameter (mm)	1200

Control Points	Head (m)	Flow (l/s)	Control Points	Head (m)	Flow (l/s)
Design Point (Calculated)	1.500	5.6	Kick-Flo®	0.921	4.4
Flush-Flo™	0.452	5.6	Mean Flow over Head Range		4.9

The hydrological calculations have been based on the Head/Discharge relationship for the Hydro-Brake Optimum® as specified. Should another type of control device other than a Hydro-Brake Optimum® be utilised then these storage routing calculations will be invalidated.

Depth (m)	Flow (l/s)								
0.100	3.5	0.800	5.1	2.000	6.4	4.000	8.8	7.000	11.5
0.200	5.0	1.000	4.6	2.200	6.7	4.500	9.3	7.500	11.9
0.300	5.4	1.200	5.0	2.400	6.9	5.000	9.8	8.000	12.3
0.400	5.5	1.400	5.4	2.600	7.2	5.500	10.3	8.500	12.6
0.500	5.5	1.600	5.7	3.000	7.7	6.000	10.7	9.000	13.0
0.600	5.5	1.800	6.1	3.500	8.3	6.500	11.1	9.500	13.3

Storage Structures for West StormCellular Storage Manhole: SW10, DS/PN: SW1.005

Invert Level (m) 75.299 Safety Factor 2.0
 Infiltration Coefficient Base (m/hr) 0.00000 Porosity 0.95
 Infiltration Coefficient Side (m/hr) 0.00000

Depth (m)	Area (m²)	Inf. Area (m²)	Depth (m)	Area (m²)	Inf. Area (m²)	Depth (m)	Area (m²)	Inf. Area (m²)
0.000	685.0	0.0	3.600	0.0	0.0	7.200	0.0	0.0
0.400	685.0	0.0	4.000	0.0	0.0	7.600	0.0	0.0
0.800	685.0	0.0	4.400	0.0	0.0	8.000	0.0	0.0
1.200	0.0	0.0	4.800	0.0	0.0	8.400	0.0	0.0
1.600	0.0	0.0	5.200	0.0	0.0	8.800	0.0	0.0
2.000	0.0	0.0	5.600	0.0	0.0	9.200	0.0	0.0
2.400	0.0	0.0	6.000	0.0	0.0	9.600	0.0	0.0
2.800	0.0	0.0	6.400	0.0	0.0	10.000	0.0	0.0
3.200	0.0	0.0	6.800	0.0	0.0			

TRP Consulting The Landmark 21 Back Turner Street Manchester		Page 6
Date 23/06/2015 09:28 File 6751 Logistics drainage Micro Drainage	Designed by timr Checked by Network 2014.1	

Summary of Critical Results by Maximum Level (Rank 1) for West Storm

Simulation Criteria

Areal Reduction Factor 1.000 Additional Flow = % of Total Flow 0.000
 Hot Start (mins) 0 MADD Factor * 10m³/ha Storage 2.000
 Hot Start Level (mm) 0 Inlet Coeffiecient 0.800
 Manhole Headloss Coeff (Global) 0.500 Flow per Person per Day (l/per/day) 0.000
 Foul Sewage per hectare (l/s) 0.000

Number of Input Hydrographs 0 Number of Offline Controls 0 Number of Time/Area Diagrams 0
 Number of Online Controls 1 Number of Storage Structures 1 Number of Real Time Controls 0

Synthetic Rainfall Details

Rainfall Model FSR M5-60 (mm) 18.900 Cv (Summer) 0.750
 Region England and Wales Ratio R 0.300 Cv (Winter) 0.840

Margin for Flood Risk Warning (mm) 300.0
 Analysis Timestep 2.5 Second Increment (Extended)
 DTS Status OFF
 DVD Status ON
 Inertia Status OFF

Profile(s) Summer and Winter
 Duration(s) (mins) 15, 30, 60, 120, 240, 360, 480, 960, 1440
 Return Period(s) (years) 1, 30, 100
 Climate Change (%) 30, 30, 30

PN	Storm	Return Period	Climate Change	First X Surcharge	First Y Flood	First Z Overflow	O/F Act.	Lvl Exc.
SW1.000	960 Winter	100	+30%	30/15	Winter			
SW1.001	960 Winter	100	+30%	30/15	Winter			
SW2.000	15 Winter	100	+30%	30/15	Summer			
SW1.002	960 Winter	100	+30%	30/15	Summer			
SW3.000	15 Winter	100	+30%	30/15	Summer			
SW1.003	960 Winter	100	+30%	30/15	Summer			
SW4.000	15 Winter	100	+30%	30/15	Summer			
SW4.001	960 Winter	100	+30%	30/15	Summer			
SW1.004	960 Winter	100	+30%	30/15	Summer			
SW1.005	960 Winter	100	+30%	30/120	Winter			
SW1.006	960 Winter	100	+30%	30/30	Winter			

PN	Water		Flooded			Pipe	
	US/MH	Level (m)	Surch'ed Depth (m)	Volume (m³)	Flow / Cap. (l/s)	O'flow (l/s)	Status
SW1.000	SW1	76.960	0.435	0.000	0.11	0.0	6.8 SURCHARGED
SW1.001	SW2	76.959	0.491	0.000	0.09	0.0	6.8 SURCHARGED
SW2.000	SW3	77.254	0.804	0.000	1.89	0.0	111.2 FLOOD RISK
SW1.002	SW4	76.958	0.683	0.000	0.16	0.0	17.9 FLOOD RISK
SW3.000	SW5	77.310	0.860	0.000	1.76	0.0	61.7 FLOOD RISK
SW1.003	SW6	76.956	0.845	0.000	0.11	0.0	24.3 FLOOD RISK
SW4.000	SW7	77.298	0.848	0.000	1.63	0.0	108.3 FLOOD RISK
SW4.001	SW8	76.957	0.681	0.000	0.15	0.0	17.6 SURCHARGED
SW1.004	SW9	76.954	1.105	0.000	0.24	0.0	41.9 SURCHARGED
SW1.005	SW10	76.953	1.129	0.000	0.06	0.0	15.1 FLOOD RISK

The Landmark
21 Back Turner Street
Manchester

Date 23/06/2015 09:28
File 6751 Logistics drainage
Micro Drainage

Designed by timr

Checked by

Network 2014.1



Summary of Critical Results by Maximum Level (Rank 1) for West Storm

PN	US/MH	Water		Flooded		Pipe	
		Name	Level (m)	Surch'd Depth (m)	Volume (m³)	Flow / O'flow Cap. (l/s)	Flow (l/s)
SW1.006	SW11	76.951		1.319	0.000	0.04	0.0 6.0 FLOOD RISE

APPENDIX C1

MICRO DRAINAGE SIMULATION OUTPUT – Eastern site network

The Landmark
21 Back Turner Street
Manchester

Date 23/06/2015 09:35

File 6751 Logistics drainage

Micro Drainage

Designed by timr

Checked by

Network 2014.1

STORM SEWER DESIGN by the Modified Rational MethodDesign Criteria for East storm

Pipe Sizes STANDARD Manhole Sizes STANDARD

FSR Rainfall Model - England and Wales

Return Period (years)	100	Add Flow / Climate Change (%)	0
M5-60 (mm)	18.900	Minimum Backdrop Height (m)	0.200
Ratio R	0.300	Maximum Backdrop Height (m)	1.500
Maximum Rainfall (mm/hr)	75	Min Design Depth for Optimisation (m)	0.900
Maximum Time of Concentration (mins)	30	Min Vel for Auto Design only (m/s)	1.00
Foul Sewage (l/s/ha)	0.000	Min Slope for Optimisation (1:X)	250
Volumetric Runoff Coeff.	0.750		

Designed with Level Soffits

Network Design Table for East storm

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Auto Design
SE1.000	24.118	0.783	30.8	0.023	5.00	0.0	0.600	o	150	⊕
SE2.000	16.615	0.284	58.5	0.022	5.00	0.0	0.600	o	150	⊕
SE1.001	96.998	0.667	145.4	0.092	0.00	0.0	0.600	o	225	⊕
SE1.002	7.776	0.200	38.9	0.014	0.00	0.0	0.600	o	225	⊕
SE3.000	53.647	0.616	87.1	0.036	5.00	0.0	0.600	o	150	⊕
SE3.001	46.150	0.193	239.1	0.538	0.00	0.0	0.600	o	450	⊕
SE4.000	4.297	0.061	70.4	0.000	5.00	0.0	0.600	o	150	⊕
SE3.002	7.881	0.026	308.0	0.000	0.00	0.0	0.600	o	450	⊕

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
SE1.000	75.00	5.22	78.100	0.023	0.0	0.0	0.0	1.82	32.2	4.7
SE2.000	75.00	5.21	77.700	0.022	0.0	0.0	0.0	1.32	23.3	4.5
SE1.001	75.00	6.71	77.242	0.138	0.0	0.0	0.0	1.08	43.0	27.9
SE1.002	75.00	6.78	76.575	0.152	0.0	0.0	0.0	2.10	83.7	30.9
SE3.000	75.00	5.83	76.450	0.036	0.0	0.0	0.0	1.08	19.0	7.2
SE3.001	75.00	6.42	75.534	0.573	0.0	0.0	0.0	1.31	208.4	116.5
SE4.000	75.00	5.06	76.500	0.000	0.0	0.0	0.0	1.20	21.2	0.0
SE3.002	75.00	6.53	75.341	0.573	0.0	0.0	0.0	1.15	183.4	116.5

TRP Consulting The Landmark 21 Back Turner Street Manchester		Page 2
Date 23/06/2015 09:35 File 6751 Logistics drainage Micro Drainage	Designed by timr Checked by Network 2014.1	

Network Design Table for East storm

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Auto Design
SE1.003	14.288	0.051	278.7	0.000	0.00	0.0	0.600	o	450	
SE5.000	26.223	0.264	99.2	0.051	5.00	0.0	0.600	o	150	
SE1.004	23.253	0.054	429.9	0.000	0.00	0.0	0.600	o	525	
SE1.005	4.033	0.104	38.7	0.000	0.00	0.0	0.600	o	525	
SE6.000	5.600	0.133	42.1	0.000	5.00	0.0	0.600	o	150	
SE6.001	15.782	0.209	75.5	0.036	0.00	0.0	0.600	o	150	
SE7.000	5.600	0.272	20.6	0.047	5.00	0.0	0.600	o	150	
SE6.002	5.365	0.104	51.7	0.000	0.00	0.0	0.600	o	150	
SE8.000	5.600	0.123	45.5	0.066	5.00	0.0	0.600	o	150	
SE8.001	22.983	0.228	100.8	0.000	0.00	0.0	0.600	o	225	
SE9.000	10.905	0.122	89.4	0.170	5.00	0.0	0.600	o	300	
SE8.002	8.281	0.035	236.6	0.036	0.00	0.0	0.600	o	375	
SE6.003	13.277	0.053	250.0	0.000	0.00	0.0	0.600	o	375	

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
SE1.003	75.00	6.97	75.316	0.725	0.0	0.0	0.0	1.21	192.9	147.3
SE5.000	75.00	5.43	76.250	0.051	0.0	0.0	0.0	1.01	17.8	10.4
SE1.004	75.00	7.33	75.190	0.777	0.0	0.0	0.0	1.07	232.5	157.7
SE1.005	75.00	7.35	75.135	0.777	0.0	0.0	0.0	3.61	780.7	157.7
SE6.000	75.00	5.06	76.270	0.000	0.0	0.0	0.0	1.56	27.5	0.0
SE6.001	75.00	5.29	76.137	0.036	0.0	0.0	0.0	1.16	20.5	7.3
SE7.000	75.00	5.04	76.250	0.047	0.0	0.0	0.0	2.23	39.4	9.5
SE6.002	75.00	5.35	75.928	0.083	0.0	0.0	0.0	1.40	24.8	16.8
SE8.000	75.00	5.06	76.210	0.066	0.0	0.0	0.0	1.50	26.4	13.4
SE8.001	75.00	5.36	76.012	0.066	0.0	0.0	0.0	1.30	51.8	13.4
SE9.000	75.00	5.11	76.397	0.170	0.0	0.0	0.0	1.66	117.6	34.4
SE8.002	75.00	5.47	75.634	0.272	0.0	0.0	0.0	1.17	129.6	55.2
SE6.003	75.00	5.67	75.599	0.354	0.0	0.0	0.0	1.14	126.1	72.0

The Landmark
21 Back Turner Street
Manchester

Date 23/06/2015 09:35
File 6751 Logistics drainage
Micro Drainage

Designed by timr

Checked by

Network 2014.1



Network Design Table for East storm

PN	Length (m)	Fall (1:X)	Slope (ha)	I.Area (mins)	T.E. (ha)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Auto Design
SE10.000	16.998	0.171	99.3	0.040	5.00	0.0	0.600	c	150	
SE6.004	23.406	0.095	245.2	0.040	0.00	0.0	0.600	c	375	
SE6.005	2.791	0.026	106.6	0.000	0.00	0.0	0.600	o	375	
SE11.000	7.342	1.594	4.6	0.091	5.00	0.0	0.600	o	150	
SE1.006	1.516	0.006	252.7	0.000	0.00	0.0	0.600	o	150	

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	E	I.Area (ha)	E Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
SE10.000	75.00	5.28	76.450		0.040	0.0	0.0	0.0	1.01	17.8	8.2
SE6.004	75.00	6.01	75.546		0.435	0.0	0.0	0.0	1.15	127.3	88.3
SE6.005	75.00	6.03	75.450		0.435	0.0	0.0	0.0	1.75	193.8	88.3
SE11.000	75.00	5.03	76.675		0.091	0.0	0.0	0.0	4.73	83.6	16.6
SE1.006	75.00	5.04	75.031		0.000	7.1	0.0	0.0	0.63	11.1	7.1

TRP Consulting The Landmark 21 Back Turner Street Manchester	Date 23/06/2015 09:35 File 6751 Logistics drainage	Designed by timr Checked by Micro Drainage Network 2014.1	Page 4
			

Manhole Schedules for East storm

MH Name	MH CL (m)	MH Depth (m)	MH Connection	MH Diam.,L*W (mm)	PN	Pipe Out Invert Level (m)	Diameter (mm)	PN	Pipes In Invert Level (m)	Diameter (mm)	Backdrop (mm)
SE1	79.200	1.100	Open Manhole	1200	SE1.000	78.100	150				
SE2	78.700	1.000	Open Manhole	1200	SE2.000	77.700	150				
SE3	78.500	1.258	Open Manhole	1200	SE1.001	77.242	225	SE1.000	77.317	150	
								SE2.000	77.416	150	99
SE4	77.700	1.125	Open Manhole	1200	SE1.002	76.575	225	SE1.001	76.575	225	
SE5	77.500	1.050	Open Manhole	1200	SE3.000	76.450	150				
SE6	77.500	1.966	Open Manhole	1350	SE3.001	75.534	450	SE3.000	75.834	150	
SE7	77.520	1.020	Open Manhole	1200	SE4.000	76.500	150				
SE8	77.400	2.059	Open Manhole	1350	SE3.002	75.341	450	SE3.001	75.341	450	
								SE4.000	76.439	150	798
SE9	77.600	2.284	Open Manhole	1350	SE1.003	75.316	450	SE1.002	76.375	225	834
								SE3.002	75.316	450	
SE10	77.300	1.050	Open Manhole	1200	SE5.000	76.250	150				
SE11	77.700	2.510	Open Manhole	1500	SE1.004	75.190	525	SE1.003	75.265	450	
								SE5.000	75.986	150	421
SE12	78.000	2.865	Open Manhole	1500	SE1.005	75.135	525	SE1.004	75.135	525	
SE13	77.270	1.000	Open Manhole	1200	SE6.000	76.270	150				
SE14	77.137	1.000	Open Manhole	1200	SE6.001	76.137	150	SE6.000	76.137	150	
SE15	77.250	1.000	Open Manhole	1200	SE7.000	76.250	150				
SE16	77.137	1.209	Open Manhole	1200	SE6.002	75.928	150	SE6.001	75.928	150	
								SE7.000	75.978	150	50
SE17	77.260	1.050	Open Manhole	1200	SE8.000	76.210	150				
SE18	77.137	1.125	Open Manhole	1200	SE8.001	76.012	225	SE8.000	76.087	150	
SE19	77.450	1.053	Open Manhole	1200	SE9.000	76.397	300				
SE20	77.137	1.503	Open Manhole	1350	SE8.002	75.634	375	SE8.001	75.784	225	
								SE9.000	76.275	300	566
SE21	77.137	1.538	Open Manhole	1350	SE6.003	75.599	375	SE6.002	75.824	150	
								SE8.002	75.599	375	
SE22	77.500	1.050	Open Manhole	1200	SE10.000	76.450	150				
SE23	77.500	1.954	Open Manhole	1350	SE6.004	75.546	375	SE6.003	75.546	375	
								SE10.000	76.279	150	508
SE24	78.000	2.550	Open Manhole	1350	SE6.005	75.450	375	SE6.004	75.450	375	
SE25	77.800	1.125	Open Manhole	1200	SE11.000	76.675	150				
SE26	77.800	2.769	Open Manhole	1500	SE1.006	75.031	150	SE1.005	75.031	525	
								SE6.005	75.424	375	618
								SE11.000	75.081	150	50
SE	77.810	2.785	Open Manhole	0		OUTFALL		SE1.006	75.025	150	

TRP Consulting The Landmark 21 Back Turner Street Manchester	Date 23/06/2015 09:35 File 6751 Logistics drainage Micro Drainage	Designed by timer Checked by Network 2014.1	Page 5
---	---	---	--------



Pipeline Schedules for East storm

Upstream Manhole

PN	Hyd Sect	Diam (mm)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
SE1.000	c	150	SE1	79.200	78.100	0.950	Open Manhole	1200
SE2.000	c	150	SE2	78.700	77.700	0.850	Open Manhole	1200
SE1.001	o	225	SE3	78.500	77.242	1.033	Open Manhole	1200
SE1.002	c	225	SE4	77.700	76.575	0.900	Open Manhole	1200
SE3.000	c	150	SE5	77.500	76.450	0.900	Open Manhole	1200
SE3.001	o	450	SE6	77.500	75.534	1.516	Open Manhole	1350
SE4.000	o	150	SE7	77.520	76.500	0.870	Open Manhole	1200
SE3.002	c	450	SE8	77.400	75.341	1.609	Open Manhole	1350
SE1.003	o	450	SE9	77.600	75.316	1.834	Open Manhole	1350
SE5.000	c	150	SE10	77.300	76.250	0.900	Open Manhole	1200
SE1.004	o	525	SE11	77.700	75.190	1.985	Open Manhole	1500
SE1.005	o	525	SE12	78.000	75.135	2.340	Open Manhole	1500
SE6.000	o	150	SE13	77.270	76.270	0.850	Open Manhole	1200

Downstream Manhole

PN	Length (m)	Slope (1:X)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
SE1.000	24.118	30.8	SE3	78.500	77.317	1.033	Open Manhole	1200
SE2.000	16.615	58.5	SE3	78.500	77.416	0.934	Open Manhole	1200
SE1.001	96.998	145.4	SE4	77.700	76.575	0.900	Open Manhole	1200
SE1.002	7.776	38.9	SE9	77.600	76.375	1.000	Open Manhole	1350
SE3.000	53.647	87.1	SE6	77.500	75.834	1.516	Open Manhole	1350
SE3.001	46.150	239.1	SE8	77.400	75.341	1.609	Open Manhole	1350
SE4.000	4.297	70.4	SE8	77.400	76.439	0.811	Open Manhole	1350
SE3.002	7.881	308.0	SE9	77.600	75.316	1.834	Open Manhole	1350
SE1.003	14.288	278.7	SE11	77.700	75.265	1.985	Open Manhole	1500
SE5.000	26.223	99.2	SE11	77.700	75.986	1.564	Open Manhole	1500
SE1.004	23.253	429.9	SE12	78.000	75.135	2.340	Open Manhole	1500
SE1.005	4.033	38.7	SE26	77.800	75.031	2.244	Open Manhole	1500
SE6.000	5.600	42.1	SH14	77.137	76.137	0.850	Open Manhole	1200

TRP Consulting The Landmark 21 Back Turner Street Manchester		Page 6
Date 23/06/2015 09:35 File 6751 Logistics drainage Micro Drainage	Designed by timr Checked by Network 2014.1	

PIPELINE SCHEDULES for East storm

Upstream Manhole

PN	Hyd Sect	Diam (mm)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM. (mm)	L*W
SE6.001	o	150	SE14	77.137	76.137	0.850	Open Manhole	1200	
SE7.000	o	150	SE15	77.250	76.250	0.850	Open Manhole	1200	
SE6.002	o	150	SE16	77.137	75.928	1.059	Open Manhole	1200	
SE8.000	o	150	SE17	77.260	76.210	0.900	Open Manhole	1200	
SE8.001	o	225	SE18	77.137	76.012	0.900	Open Manhole	1200	
SE9.000	o	300	SE19	77.450	76.397	0.753	Open Manhole	1200	
SE8.002	o	375	SE20	77.137	75.634	1.128	Open Manhole	1350	
SE6.003	o	375	SE21	77.137	75.599	1.163	Open Manhole	1350	
SE10.000	o	150	SE22	77.500	76.450	0.900	Open Manhole	1200	
SE6.004	o	375	SE23	77.500	75.546	1.579	Open Manhole	1350	
SE6.005	o	375	SE24	78.000	75.450	2.175	Open Manhole	1350	
SE11.000	o	150	SE25	77.800	76.675	0.975	Open Manhole	1200	

Downstream Manhole

PN	Length (m)	Slope (1:X)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
SE6.001	15.782	75.5	SE16	77.137	75.928	1.059	Open Manhole	1200
SE7.000	5.600	20.6	SE16	77.137	75.978	1.009	Open Manhole	1200
SE6.002	5.365	51.7	SE21	77.137	75.824	1.163	Open Manhole	1350
SE8.000	5.600	45.5	SE18	77.137	76.087	0.900	Open Manhole	1200
SE8.001	22.983	100.8	SE20	77.137	75.784	1.128	Open Manhole	1350
SE9.000	10.905	89.4	SE20	77.137	76.275	0.562	Open Manhole	1350
SE8.002	8.281	236.6	SE21	77.137	75.599	1.163	Open Manhole	1350
SE6.003	13.277	250.0	SE23	77.500	75.546	1.579	Open Manhole	1350
SE10.000	16.998	99.3	SE23	77.500	76.279	1.071	Open Manhole	1350
SE6.004	23.406	245.2	SE24	78.000	75.450	2.175	Open Manhole	1350
SE6.005	2.791	106.6	SE26	77.800	75.424	2.001	Open Manhole	1500
SE11.000	7.342	4.6	SE26	77.800	75.081	2.569	Open Manhole	1500

The Landmark
21 Back Turner Street
Manchester

Date 23/06/2015 09:35
File 6761 Logistics drainage
Micro Drainage

Designed by timer
Checked by
Network 2014.1



Pipeline Schedules for East storm

Upstream Manhole

PN	Hyd Sect	Diam	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
SE1.006	o	150	SE26	77.800	75.031	2.619	Open Manhole	1500

Downstream Manhole

PN	Length (m)	Slope (1:X)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
SE1.006	1.516	252.7	SE	77.810	75.025	2.635	Open Manhole	6

Free Flowing Outfall Details for East storm

Outfall Pipe Number	Outfall Name	C. Level (m)	I. Level (m)	Min I. Level (mm)	D,L (mm)	W (m)
SE1.006	SE	77.810	75.025	75.000	0	0

Simulation Criteria for East storm

Volumetric Runoff Coeff	0.750	Additional Flow - % of Total Flow	0.000
Areal Reduction Factor	1.000	MADD Factor * 10m³/ha	Storage 2.000
Hot Start (mins)	0	Inlet Coefficient	0.800
Hot Start Level (mm)	0	Flow per Person per Day (l/per/day)	0.000
Manhole Headloss Coeff (Global)	0.500	Run Time (mins)	60
Foul Sewage per hectare (l/s)	0.000	Output Interval (mins)	1

Number of Input Hydrographs 0 Number of Offline Controls 0 Number of Time/Area Diagrams 0
Number of Online Controls 1 Number of Storage Structures 7 Number of Real Time Controls 0

Synthetic Rainfall Details

Rainfall Model	FSR	Profile Type	Summer
Return Period (years)	100	Cv (Summer)	0.750
Region England and Wales		Cv (Winter)	0.940
M5-60 (mm)	18.900	Storm Duration (mins)	30
Ratio R	0.300		

TRP Consulting The Landmark 21 Back Turner Street Manchester		Page 8
Date 23/06/2015 09:35 File 6751 Logistics drainage Micro Drainage	Designed by timr Checked by Network 2014.1	

Online Controls for East storm

Hydro-Brake Optimum® Manhole: SE26, DS/PN: SE1.006, Volume (m³): 5.7

Unit Reference MD-SHE-0118-7200-1500-7200	
Design Head (m)	1.500
Design Flow (l/s)	7.2
Flush-Flo™	Calculated
Objective	Minimise upstream storage
Diameter (mm)	118
Invert Level (m)	75.031
Minimum Outlet Pipe Diameter (mm)	150
Suggested Manhole Diameter (mm)	1200

Control Points	Head (m)	Flow (l/s)	Control Points	Head (m)	Flow (l/s)
Design Point (Calculated)	1.500	7.2	Kick-Flo®	0.926	5.7
Flush-Flo™	0.447	7.2	Mean Flow over Head Range		6.3

The hydrological calculations have been based on the Head/Discharge relationship for the Hydro-Brake Optimum® as specified. Should another type of control device other than a Hydro-Brake Optimum® be utilised then these storage routing calculations will be invalidated

Depth (m)	Flow (l/s)								
0.100	4.2	0.800	6.6	2.000	8.2	4.000	11.4	7.000	14.9
0.200	6.5	1.000	6.0	2.200	8.6	4.500	12.1	7.500	15.4
0.300	7.0	1.200	6.5	2.400	9.0	5.000	12.7	8.000	15.9
0.400	7.2	1.400	7.0	2.600	9.3	5.500	13.3	8.500	16.4
0.500	7.2	1.600	7.4	3.000	10.0	6.000	13.9	9.000	16.8
0.600	7.1	1.800	7.8	3.500	10.7	6.500	14.4	9.500	17.3

TRP Consulting The Landmark 21 Back Turner Street Manchester		Page 9
Date 23/06/2015 09:35 File 6751 Logistics drainage Micro Drainage	Designed by timx Checked by Network 2014.1	

Storage Structures for East storm

Dry Swale Manhole: SE6, DS/PN: SE3.001

Warning:- Volume should always be included unless the upstream pipe is being used for storage and/or as a carrier

Infiltration Coefficient Base (m/hr)	0.00000	Trench Length (m)	88.4
Infiltration Coefficient Side (m/hr)	0.00000	Side Slope (1:X)	4.0
Safety Factor	2.0	Slope (1:X)	0.0
Porosity	0.90	Cap Volume Depth (m)	0.900
Invert Level (m)	75.534	Cap Infiltration Depth (m)	0.000
Trench Height (m)	0.600	Include Swale Volume	Yes
Trench Width (m)	1.0		

Cellular Storage Manhole: SE11, DS/PN: SE1.004

Invert Level (m)	75.190	Safety Factor	2.0
Infiltration Coefficient Base (m/hr)	0.00000	Porosity	0.95
Infiltration Coefficient Side (m/hr)	0.00000		

Depth (m)	Area (m ²)	Inf. Area (m ²)	Depth (m)	Area (m ²)	Inf. Area (m ²)	Depth (m)	Area (m ²)	Inf. Area (m ²)
0.000	650.0	0.0	3.600	0.0	0.0	7.200	0.0	0.0
0.400	650.0	0.0	4.000	0.0	0.0	7.600	0.0	0.0
0.800	650.0	0.0	4.400	0.0	0.0	8.000	0.0	0.0
1.200	650.0	0.0	4.800	0.0	0.0	8.400	0.0	0.0
1.600	650.0	0.0	5.200	0.0	0.0	8.800	0.0	0.0
2.000	650.0	0.0	5.600	0.0	0.0	9.200	0.0	0.0
2.400	650.0	0.0	6.000	0.0	0.0	9.600	0.0	0.0
2.800	650.0	0.0	6.400	0.0	0.0	10.000	0.0	0.0
3.200	650.0	0.0	6.800	0.0	0.0			

Dry Swale Manhole: SE13, DS/PN: SE6.000

Warning:- Volume should always be included unless the upstream pipe is being used for storage and/or as a carrier

Infiltration Coefficient Base (m/hr)	0.00000	Trench Length (m)	10.6
Infiltration Coefficient Side (m/hr)	0.00000	Side Slope (1:X)	4.0
Safety Factor	2.0	Slope (1:X)	0.0
Porosity	0.90	Cap Volume Depth (m)	0.850
Invert Level (m)	76.270	Cap Infiltration Depth (m)	0.000
Trench Height (m)	0.600	Include Swale Volume	Yes
Trench Width (m)	0.4		

Dry Swale Manhole: SE15, DS/PN: SE7.000

Warning:- Volume should always be included unless the upstream pipe is being used for storage and/or as a carrier

Infiltration Coefficient Base (m/hr)	0.00000	Porosity	0.90
Infiltration Coefficient Side (m/hr)	0.00000	Invert Level (m)	76.250
Safety Factor	2.0	Trench Height (m)	0.600

TRP Consulting The Landmark 21 Back Turner Street Manchester		Page 10
Date 23/06/2015 09:35 File 6751 Logistics drainage Micro Drainage	Designed by timr Checked by Network 2014.1	

Dry Swale Manhole: SE15, DS/PN: SE7.000

Trench Width (m) 0.4 Cap Volume Depth (m) 0.850
Trench Length (m) 24.4 Cap Infiltration Depth (m) 0.000
Side Slope (1:X) 4.0 Include Swale Volume Yes
Slope (1:X) 0.0

Dry Swale Manhole: SE19, DS/PN: SE9.000

Warning:-- Volume should always be included unless the upstream pipe is being used for storage and/or as a carrier

Infiltration Coefficient Base (m/hr) 0.00000	Trench Length (m) 16.7
Infiltration Coefficient Side (m/hr) 0.00000	Side Slope (1:X) 4.0
Safety Factor 2.0	Slope (1:X) 0.0
Porosity 0.90	Cap Volume Depth (m) 0.950
Invert Level (m) 76.397	Cap Infiltration Depth (m) 0.000
Trench Height (m) 0.600	Include Swale Volume Yes
Trench Width (m) 0.4	

Cellular Storage Manhole: SE24, DS/PN: SE6.005

Invert Level (m) 75.419 Safety Factor 2.0
Infiltration Coefficient Base (m/hr) 0.00000 Porosity 0.95
Infiltration Coefficient Side (m/hr) 0.00000

Depth (m)	Area (m ²)	Inf. Area (m ²)	Depth (m)	Area (m ²)	Inf. Area (m ²)	Depth (m)	Area (m ²)	Inf. Area (m ²)
0.000	650.0	0.0	3.600	0.0	0.0	7.200	0.0	0.0
0.400	650.0	0.0	4.000	0.0	0.0	7.600	0.0	0.0
0.800	650.0	0.0	4.400	0.0	0.0	8.000	0.0	0.0
1.200	0.0	0.0	4.800	0.0	0.0	8.400	0.0	0.0
1.600	0.0	0.0	5.200	0.0	0.0	8.800	0.0	0.0
2.000	0.0	0.0	5.600	0.0	0.0	9.200	0.0	0.0
2.400	0.0	0.0	6.000	0.0	0.0	9.600	0.0	0.0
2.800	0.0	0.0	6.400	0.0	0.0	10.000	0.0	0.0
3.200	0.0	0.0	6.800	0.0	0.0			

Dry Swale Manhole: SE25, DS/PN: SE11.000

Warning:-- Volume should always be included unless the upstream pipe is being used for storage and/or as a carrier

Infiltration Coefficient Base (m/hr) 0.00000	Trench Length (m) 42.0
Infiltration Coefficient Side (m/hr) 0.00000	Side Slope (1:X) 4.0
Safety Factor 2.0	Slope (1:X) 0.0
Porosity 0.30	Cap Volume Depth (m) 1.000
Invert Level (m) 76.675	Cap Infiltration Depth (m) 0.000
Trench Height (m) 0.600	Include Swale Volume Yes
Trench Width (m) 0.4	

The Landmark
21 Back Turner Street
Manchester

Date 23/06/2015 09:35
File 6751 Logistics drainage
Micro Drainage

Designed by timr

Checked by

Network 2014.1


Summary of Critical Results by Maximum Level (Rank 1) for East storm
Simulation Criteria

Areal Reduction Factor 1.000 Additional Flow = % of Total Flow 0.000
 Hot Start (mins) 0 MADD Factor * 10m³/ha Storage 2.000
 Hot Start Level (mm) 0 Inlet Coefficient 0.800
 Manhole Headloss Coeff (Global) 0.500 Flow per Person per Day (l/per/day) 0.000
 Foul Sewage per hectare (l/s) 0.000

Number of Input Hydrographs 0 Number of Offline Controls 0 Number of Time/Area Diagrams 0
 Number of Online Controls 1 Number of Storage Structures 7 Number of Real Time Controls 0

Synthetic Rainfall Details

Rainfall Model FSR M5-60 (mm) 18.900 Cv (Summer) 0.750
 Region England and Wales Ratio R 0.300 Cv (Winter) 0.840

Margin for Flood Risk Warning (mm)	300.0
Analysis Timestep 2.5 Second Increment (Extended)	
DTS Status	OFF
DVD Status	ON
Inertia Status	OFF

Profile(s)	Summer and Winter
Duration(s) (mins)	15, 30, 60, 120, 240, 360, 480, 960, 1440
Return Period(s) (years)	1, 30, 100
Climate Change (%)	30, 30, 30

PN	Storm	Return Period	Climate Change	First X Surcharge	First Y Flood	First Z Overflow	O/F Act.	Lvl Exc.
SE1.000	15 Winter	100	+30%					
SE2.000	15 Winter	100	+30%	100/15	Summer			
SE1.001	15 Winter	100	+30%	30/15	Summer			
SE1.002	15 Winter	100	+30%					
SE3.000	15 Winter	100	+30%					
SE3.001	30 Winter	100	+30%	100/15	Winter			
SE4.000	15 Winter	30	+30%					
SE3.002	960 Winter	100	+30%	30/15	Winter			
SE1.003	960 Winter	100	+30%	30/15	Summer			
SE5.000	15 Winter	100	+30%	30/15	Summer			
SE1.004	960 Winter	100	+30%	30/240	Winter			
SE1.005	960 Winter	100	+30%	30/120	Winter			
SE6.000	15 Winter	100	+30%	100/15	Winter			
SE6.001	15 Winter	100	+30%	30/15	Summer			
SE7.000	15 Winter	100	+30%	100/15	Summer			
SE6.002	15 Winter	100	+30%	30/15	Summer			
SE8.000	15 Winter	100	+30%	30/15	Summer			
SE8.001	15 Winter	100	+30%	30/15	Winter			
SE9.000	15 Winter	100	+30%					
SE8.002	15 Winter	100	+30%	30/15	Summer			
SE6.003	15 Winter	100	+30%	30/15	Summer			
SE10.000	15 Winter	100	+30%	100/15	Summer			
SE6.004	15 Winter	100	+30%	30/15	Summer			
SE6.005	960 Winter	100	+30%	100/240	Winter			
SE11.000	15 Winter	100	+30%					
SE1.006	960 Winter	100	+30%	1/15	Summer			


TRP Consulting The Landmark 21 Back Turner Street Manchester		Page 12
Date 23/06/2015 09:35 File 6751 Logistics drainage Micro Drainage	Designed by timr Checked by Network 2014.1	

Summary of Critical Results by Maximum Level (Rank 1) for East storm

PN	US/MH	Water		Flooded			Pipe	
		Name	Level (m)	Surch'd ed Depth (m)	Volume (m³)	Flow / O'flow Cap. (l/s)	Flow (l/s)	Status
SE1.000	SE1	78.164	-0.086	0.000	0.37	0.0	11.4	OK
SE2.000	SE2	78.124	0.274	0.000	0.56	0.0	12.1	SURCHARGED
SE1.001	SE3	78.075	0.608	0.000	1.31	0.0	55.0	SURCHARGED
SE1.002	SE4	76.749	-0.051	0.000	0.94	0.0	59.4	OK
SE3.000	SE5	76.565	-0.035	0.000	0.92	0.0	17.1	OK
SE3.001	SE6	76.039	0.054	0.000	0.88	0.0	164.7	SURCHARGED
SE4.000	SE7	76.500	-0.150	0.000	0.00	0.0	0.0	OK
SE3.002	SE8	75.985	0.193	0.000	0.19	0.0	22.4	SURCHARGED
SE1.003	SE9	75.984	0.218	0.000	0.19	0.0	28.3	SURCHARGED
SE5.000	SE10	76.631	0.231	0.000	1.36	0.0	23.1	SURCHARGED
SE1.004	SE11	75.983	0.268	0.000	0.06	0.0	11.7	SURCHARGED
SE1.005	SE12	75.985	0.324	0.000	0.04	0.0	11.1	SURCHARGED
SE6.000	SE13	76.440	0.020	0.000	0.21	0.0	4.8	SURCHARGED
SE6.001	SE14	76.448	0.161	0.000	0.72	0.0	13.6	SURCHARGED
SE7.000	SE15	76.462	0.062	0.000	0.60	0.0	19.4	SURCHARGED
SE6.002	SE16	76.390	0.312	0.000	1.58	0.0	32.0	SURCHARGED
SE8.000	SE17	76.658	0.298	0.000	1.34	0.0	29.1	SURCHARGED
SE8.001	SE18	76.430	0.193	0.000	0.63	0.0	30.0	SURCHARGED
SE9.000	SE19	76.630	-0.067	0.000	0.93	0.0	81.7	OK
SE8.002	SE20	76.331	0.322	0.000	1.37	0.0	125.0	SURCHARGED
SE6.003	SE21	76.230	0.256	0.000	1.51	0.0	148.8	SURCHARGED
SE10.000	SE22	76.655	0.055	0.000	1.16	0.0	19.2	SURCHARGED
SE6.004	SE23	76.085	0.164	0.000	1.69	0.0	184.9	SURCHARGED
SE6.005	SE24	75.981	0.156	0.000	0.12	0.0	11.8	SURCHARGED
SE11.000	SE25	76.762	-0.063	0.000	0.62	0.0	44.5	OK
SE1.006	SE26	75.984	0.803	0.000	0.66	0.0	7.2	SURCHARGED

APPENDIX D

Drawing 6751 D401 – Surface Water Drainage Layout



APPENDIX E

Drawing 6751 E500 -- Surface Water Diversions

