

...THE PERFECT FINISH

K1 Spray

K1 Spray is designed for use with most render spray machines. It is ideal for larger projects where the speed of machine application can offer time saving benefits. Suitable for hand application also.

One coat Require:

26 - 32kg / sq m approx.
nominal 16 - 20mm thickness

Kitemark Classifications:

Compressive Strength: CS II

Capillary Water Absorption
Category: W2

Thermal Conductivity:
P=50% - 0.44

Silicone Scraped Texture Standard 20 Colours



White*



Buttermilk



Polar White*



Stone




Champagne




York



Cream*



Powder Blue




Salmon Pink



Pewter Grey




Terracotta



Grey




Ivory



Sterling White



Arran



Sandstone




Green



Oatmeal



Cinnamon



Fintry Stone

COLOUR NOTE

- * White is the brightest white within the Scraped Texture range, however it is not brilliant white
- * Polar White is an off white shade
- * Cream has a yellow tone to it

Above: 20 standard Scraped Texture colours. Special colours are available from a customisable pallet, upon request from our Technical Support Centre.

All full colour illustrations shown in this brochure are as accurate as the printing process will allow. It is important that a sample is obtained as we recommend colours be verified against K Rend Scraped Texture samples before ordering.

Silicone FT, Polar White, Co. Londonderry.

