



Tree Risk Management Appraisal

at



**Throstle Croft, Saccary Lane,
Mellor, Lancashire, BB1 9DW**

Prepared by:

Bowland 
Tree Consultancy Ltd

September 2020

TREE RISK MANAGEMENT APPRAISAL

THROSTLE CROFT, MELLOR

CONTENTS

1. CIVIL LAW REGARDING TREE OWNERSHIP AND DUTY OF CARE
2. QTRA METHODOLOGY OVERVIEW AND APPLICATION IN MANAGEMENT DECISIONS
3. SUMMARY OF SURVEY FINDINGS AND RECOMMENDATIONS
4. TREE SURVEY SCHEDULE
5. TREE SURVEY PLAN
6. QTRA PRACTICE NOTE



Contact Details

Bowland Tree Consultancy Ltd

Unit Two

First Floor

11 Cannon Street

Preston

Lancashire

PR1 3NR

T: 01772 437150

E: info@bowlandtreeconsultancy.co.uk

**TREE RISK MANAGEMENT APPRAISAL
THROSTLE CROFT, MELLOR**

Project Details

Project No.: BTC2059

Site: Throstle Croft, Saccary Lane, Mellor, BB1 9DW

Survey Type: Individual Tree Survey

Tree(s) Considered: Within ownership boundaries, as identified by client

Report Time Frame: 12 months from date of issue

Next Inspection Date: ≈18 months from date of issue

Client: Graham Hoare

Survey Date: 2 September 2020

Surveyor: Joseph Lambert BSc(Hons) FdSc MArborA

Report Prepared by: Joseph Lambert BSc(Hons) FdSc MArborA

Report Checked by: Phill Harris MSc BSc(Hons) HND MArborA CEnv MICFor

Date of Issue: 16 November 2020

Version No: 3

1. CIVIL LAW REGARDING TREE OWNERSHIP AND DUTY OF CARE

- 1.1 Under civil law the owner of the land on which a tree stands, together with any party who has control over the tree's management, has a duty of care to take reasonable steps to prevent or minimise the risk of personal injury and/or damage to property from any tree located within the curtilage of the land in question.
- 1.2 In turn, it is accepted that these steps should normally include commissioning a qualified and experienced arboriculturist to survey the tree in order to identify and appraise any risk of harm to persons or damage to property that it may present and, where unacceptable risks are identified, taking suitable remedial action to negate or reduce those risks accordingly.

2. QTRA METHODOLOGY OVERVIEW AND APPLICATION IN MANAGEMENT DECISIONS

- 2.1 A survey was carried out in order to consider the general structural stability of the trees at the site and the associated risk of harm that they pose to persons and/or damage that they pose to property and, from this information, to make management recommendations to reduce any risks identified to be unacceptable to a level that is considered to be either tolerable or broadly acceptable (see Table 1, below).
- 2.2 The Quantified Tree Risk Assessment (QTRA) methodology utilised for the tree survey (see appended QTRA Practice Note for more details) quantifies the three components of tree failure risk, which are:
 - i. *Target* (something with potential to be harmed and/or damaged by the mechanical failure of tree parts);
 - ii. *Impact Potential*; and
 - iii. *Probability of Failure* (within the coming year).
- 2.3 The product of the three component values is the annualised 'Risk of Harm', which is a combined measure of the likelihood and the consequence of tree failure considered in terms of the loss within the coming year, and is expressed as a probability. In applying the 'Tolerability of Risk Framework' (ToR) the QTRA methodology divides the 'Risk of Harm' into three threshold values, being:
 1. *Unacceptable* (i.e. $>1/1,000$), which is unacceptable and will not ordinarily be tolerated;
 2. *Tolerable* (i.e. between $1/1,000,000$ and $1/1,000$, where the Risk of Harm will be tolerable if it is As Low As Reasonably Practicable (ALARP); but a Risk of Harm $1/10,000$ or greater will not ordinarily be Tolerable where it is imposed on others, such as the public. In the Tolerable range management decisions are informed by consideration of the benefits and costs of risk control, including benefits provided by trees that would be lost to risk control measures; and
 3. *Broadly Acceptable* ($<1/1,000,000$), which is already ALARP.
- 2.4 The QTRA advisory thresholds, (see Table 1, below) are proposed as a reasonable approach to balancing safety from falling trees with the costs of risk reduction. This approach takes account of the principles of ALARP and ToR, but does not dictate how these principles should be applied. While the thresholds can be the foundation of a robust policy for tree risk management, tree managers should make decisions based on their own situation, values and resources.

Table 1: QTRA Advisory Risk Thresholds:

Threshold	Description	Action
Risk of harm of $1/1,000$ or greater	Unacceptable - Risks will not ordinarily be tolerated	<ul style="list-style-type: none">▪ Control the risk
Risk of harm between $1/1,000$ and $1/10,000$	Unacceptable (where imposed on others) - Risks will not ordinarily be tolerated	<ul style="list-style-type: none">▪ Control the risk▪ Review the risk
	Tolerable (by agreement) Risks may be tolerated if those exposed to the risk accept it, or the tree has exceptional value	<ul style="list-style-type: none">▪ Control the risk unless there is broad stakeholder agreement to tolerate it, or the tree has exceptional value▪ Review the risk
Risk of harm between $1/10,000$ and $1/1,000,000$	Tolerable (where imposed on others) - Risks are tolerable if ALARP	<ul style="list-style-type: none">▪ Assess costs and benefits of risk control▪ Control the risk only where a significant benefit might be achieved at reasonable cost▪ Review the risk
Risk of harm less than $1/1,000,000$	Broadly Acceptable - Risk is already ALARP	<ul style="list-style-type: none">▪ No action currently required▪ Review the risk

- 2.5 As detailed in Table 1, above, a Risk of Harm less than $1/1,000,000$ is Broadly Acceptable and already

ALARP (i.e. 'as low as reasonably practicable'). A Risk of Harm 1/1,000 or greater is unacceptable and will not ordinarily be tolerated. Between these two thresholds, the Risk of Harm is in the Tolerable region of the ToR Framework and will be tolerable if it is ALARP, but a Risk of Harm 1/10,000 or greater will not ordinarily be Tolerable where it is imposed on others, such as the public. Here, management decisions are informed by consideration of the benefits and costs of risk control, including benefits provided by trees that would be lost to risk control measures.

2.6 In respect of the above the assessor (i.e. Bowland Tree Consultancy Ltd) may consider the costs of risk control when providing options for management if specifically asked to do so, but the tree owner/manager, who owns the risk and therefore exercises control over the costs, must consider the balance and make the final management decision(s).

3. SUMMARY OF SURVEY FINDINGS AND RECOMMENDATIONS

3.1 An 'Individual Tree Survey' (see 'Schedule of Operations' appended to agreed project quote) was carried out on 2 September 2020 at the site under consideration. The ownership boundaries were identified on site as the extents of the residential garden, as advised by the client, Graham Hoare, during an initial site visit prior to instruction to proceed on the quotation.

3.2 The survey identified eighteen individual trees and six groups of trees, as detailed in the appended Tree Survey Schedule (TSS) and Tree Survey Plan (TSP). The surveyed trees are in the semi-mature to mature age range and have heights of up to 23.5 metres, stem diameters of up to 630 millimetres, and maximum diametrical crown spreads of up to approximately 16 metres.

3.3 The site consists of a detached two storey residential property positioned to the centre of the site. The remainder of the site consists of formal and informal managed residential garden. There is a single vehicular access point to south-west corner of the site off Saccary Lane, which leads to an associated vehicle turning/parking area to the south of the property. The tree population is located largely towards the perimeters of the site as part of closely to moderately spaced groups along with adjacent trees on neighbouring ground.

3.4 The site is bordered to the north by north and west by moderate usage Saccary Lane, beyond which are wooded areas, agricultural pastureland and an access to a neighbouring property, to the east is a driveway to access neighbouring residential properties, along which runs a bridleway, and beyond this are the gardens associated with those properties and to the south by a wooded area on neighbouring land (see TSP)

3.5 As a component of this appraisal various targets were identified to be within falling distances of the surveyed trees, including, but not restricted to, pedestrians and vehicles and their occupants on Saccary Lane, persons using the residential property and associated gardens within the curtilage of the client's property itself, persons using neighbouring residential garden areas, persons using the neighbouring bridleway to the east and various items of property including the residential property itself and items of garden furniture, as well as boundary features and overhead utilities.

3.6 In turn, as highlighted with the colour orange in the appended Tree Survey Schedule and in Table 2 (overleaf), the risk assessment established that T7, T13 and T18 and group G3 have calculated QTRA risk indices that fall within the unacceptable risk threshold range of 1/10,000 or over (please refer to Table 1, on the previous page, with regard to advisory tree risk thresholds). Consequently, as also detailed in Table Two, recommendations are made in order to negate the risk that they present.

3.7 However, as also detailed in Table 2 (overleaf), various works have been recommended to several of the surveyed trees with calculated QTRA risk indices that fall within the tolerable and broadly acceptable risk threshold ranges (as highlighted with the colours yellow and green, respectively), either for general non-risk management related reasons (as denoted with the suffix (M)) or, where applicable, to enable applicable trees to be inspected in further detail for risk assessment purposes (as denoted with the suffix (I)).

Table 2: Tree Work Recommendations:

No.	Species	Management Works Recommended*	Responsible Professional	Work Priority
T1	Common Lime	1. Prune tree to remove basal shoots to facilitate future inspections of stem (I). 2. Prune tree to obtain a ground clearance of approximately 3.5m over driveway (M).	1. Tree contractor 2. Tree contractor	1. Moderate 2. Low
T2	Sycamore	1. Sever ivy around stem circumference from ground level to a height of approximately 2m, and remove ivy section between (I).	1. Tree contractor	1. High
T3	Copper Beech	1. Prune tree to obtain a ground clearance of approximately 2.5m over lawn (M).	1. Tree contractor	1. Moderate
T4	Common Holly	1. Prune tree to reduce to a height of approximately 3m and reduce remaining foliage by approximately 2m on east side to remove stems with progressive subsidence and those conflicting with canopy of Beech T3 and to provide clearance to lawn to east (M).	1. Tree contractor	1. Moderate
T5	Common Oak	1. Prune tree to remove deadwood >50mm diameter overhanging adjacent road (M).	1. Tree contractor	1. Moderate
T6	Copper Beech	1. Prune tree to reduce canopy to south-east to obtain a clearance of approximately 2.5m from adjacent residential property and to obtain a clearance of approximately 2.5m over lawn (M).	1. Tree contractor	1. Moderate
T7	Sycamore	1. Remove tree due to identified increased risk of main stem failure and subsequent unacceptable risk of harm to persons.	1. Tree contractor	1. High
T8	Sycamore	1. Sever ivy around stem circumference from ground level to a height of approximately 2m, and remove ivy section between (I). 2. Remove deadwood >75mm diameter (M).	1. Tree contractor	1. High 2. Moderate
T9	Lime	1. Sever ivy around stem circumference from ground level to a height of approximately 6m, and remove ivy section between, and to prune tree to remove basal growth between ground level and a height of approximately 6m.	1. Tree contractor	1. High
T11	Common Oak	1. Prune tree to remove deadwood >50mm diameter over bridleway (M) and to obtain a ground clearance of approximately 2.5m over lawn (M).	1. Tree contractor	1. Moderate
T12	Silver Birch	1. Prune tree to obtain a ground clearance of approximately 2.5m over lawn (M).	1. Tree contractor	1. Low
T13	Common Beech	1. Remove tree due to identified increased risk of upper stem failure and unacceptable risk of damage to property.	1. Tree contractor	1. High
T15	Wild Cherry	1. Sever ivy at ground level around entire stem circumference and a height of approximately 2m and remove section in between in order to prevent dominance in canopy and facilitate future inspections (M).	1. Tree contractor	1. Moderate
T18	Common Oak	1. Inform tree owner of findings of report. 2. Instruct tree contractor to remove tree due to incipient signs of failure and subsequent unacceptable risk of harm to persons.	1. Client 2. Tree owner	1. High
G2	1no. Common Holly, 1no. Silver Birch	1. Sever ivy around stem circumference from ground level to a height of approximately 2m, and remove ivy section between to prevent dominance within canopy (M).	1. Tree contractor	1. Moderate

Continued overleaf

Table 2: Tree Work Recommendations (Continued):

No.	Species	Management Works Recommended*	Responsible Professional	Work Priority
G3	4no. Holly, 1no. Acer sp., 1no. Birch, 1no. Damson, 1no. Cherry, 1no. Sycamore	1. Prune Hollies to remove dead stems over road due to identified increased risk of failure and subsequent unacceptable risk of harm to persons. 2. Sever ivy around Sycamore's stem circumference from ground level to a height of approximately 2m, and remove ivy section between to prevent dominance within canopy (M).	1. Tree contractor 2. Tree contractor	1. High 2. High
G4	4no. Sycamore	1. Sever ivy around stem circumferences from ground level to a height of approximately 2m, and remove ivy section between (I). 2. Prune to remove deadwood >75mm diameter over bridleway (M).	1. Tree contractor 2. Tree contractor	1. High 2. Moderate
G5	3no. Common Lime, 1no. Sycamore	1. Prune Limes to remove basal growth between ground level and a height of approximately 6m. NB: Client to inform tree consultant on completion of works (I). 2. Prune canopies to obtain a 4m ground clearance over driveway to east and a 1.5m clearance from garage and greenhouse roof (M).	1. Tree contractor 2. Tree contractor	1. High 2. Low
G6	4no. Common Ash	1. Remove tree to west that is conflicting with Lime due to poor form and limited future potential (M).	1. Tree contractor	1. Low

*Note: it shall be the client's responsibility to arrange contact with the applicable local council's planning department in order to check for the presence of any statutory tree protection measures, such as the site's location within a Conservation Area and/or the presence of any Tree Preservation Orders, prior to scheduling or carrying out any tree works

3.8 Table 3, below, details the trees that are recommended for more detailed inspections for risk management related reasons following any works recommended in Table 2, along with their accompanying re-inspection schedule.

Table 3: Tree Re-Inspection Recommendations:

No.	Species	Re-Inspection Recommendations*	When?
T2	Sycamore	▪ Re-inspect tree following removal and dieback of ivy.	Within 3 months of date of report
T8	Sycamore	▪ Re-inspect tree following removal and dieback of ivy.	Within 3 months of date of report
T9	Lime	▪ Re-inspect tree following removal of basal growth and removal and dieback of ivy.	Within 3 months of date of report
G4	4no. Sycamore	▪ Re-inspect trees following removal and dieback of ivy.	Within 3 months of date of report
G5	3no. Common Lime, 1no. Sycamore	▪ Re-inspect trees following removal of basal growth.	Within 3 months of date of report

*Note: Unless otherwise specified, all inspections detailed in Table 3 are to be carried out by the project tree consultant

3.9 In consideration of the moderate usage of various areas, both adjacent to and within the site, and the associated identified targets such as persons using the client's garden and neighbouring gardens, it is subsequently recommended that all of the retained trees be re-inspected on a cyclical programme of roughly every 18 months, so that they can be alternately viewed whilst in and out of leaf in order to monitor both their structural and physiological condition and, consequently, for the site occupiers to meet their duty of care. In this respect it is therefore recommended that the trees be re-inspected during winter 2021/2022.

Site: Throstle Croft, Saccary Lane, Mellor, Lancashire, BB1 9DW

Client: Graham Hoare

Brief: Carry out an individual tree survey within area identified by client, report on projected risk posed to persons and property, and make management recommendations where appropriate

Surveyor: Joseph Lambert BSc(Hons) FdSc MARborA

Survey Date: 2 September 2020

Viewing Conditions: Overcast with prolonged heavy rain

Job Reference: BTC2059

Page: 1 of 8

No.	Species	Age	Height (m)	Stem Diam. (mm)	Crown Spread (m)	Vitality	Comments	Management Recommendations	Risk Assessment Description (Part/Target)	Target	Size	P.O.F	Reduced Mass %	Risk Index	Work Priority
T1	Common Lime	M	23	510	14	G	<ul style="list-style-type: none"> Approximately four established basal shoots up to approximately 90mm diameter growing from ground level to north against stem. Canopy low over driveway to north. 	<ul style="list-style-type: none"> Tree contractor to prune tree to remove basal shoots to facilitate future inspections of stem (I). Tree contractor to prune tree to obtain a ground clearance of approximately 3.5m over driveway (M). 	P = Deadwood up to approximately 60mm diameter. T = Persons using access driveway to property.	3	4	2	25%	<1M	L
T2	Sycamore	M	17.5	1x420 1x410 1x320 (ms)	14	G	<ul style="list-style-type: none"> Three stems arise from ground level with slightly tight unions. Stem arising to west has moderately dense ivy cover which impeded inspection. Moderate deadwood up to approximately 70mm diameter within inner canopy. 	<ul style="list-style-type: none"> Tree contractor to sever ivy around stem circumference from ground level to a height of approximately 2m, and remove ivy section between (I). NB: Client to inform tree consultant on dieback of ivy. Tree consultant to re-inspect stem and buttresses following removal and dieback of ivy. NBB: QTRA index to be re-calculated following re-inspection. 	P = Deadwood up to approximately 70mm diameter. T = Persons using garden area below tree canopy	4	4	2	50%	<1M	H

HEADINGS & ABBREVIATIONS

NO.

TREE/GROUP REFERENCE NUMBER. REFER TO PLAN OR NUMBERED TAGS WHERE APPLICABLE

SPECIES:

COMMON NAME

AGE:

Y = YOUNG, SM = SEMI MATURE, EM = EARLY MATURE, M = MATURE, PM = POST MATURE

HEIGHT:

APPROXIMATELY 80% OF TREES ARE MEASURED USING AN ELECTRONIC CLINOMETER AND THE REMAINDER ESTIMATED AGAINST THE MEASURED TREES

DIAMETER:

STEM DIAMETER MEASURED OR ESTIMATED AT A HEIGHT OF APPROXIMATELY 1.3 METRES

CROWN SPREAD:

MEASURED OR ESTIMATED DIAMETER OF CROWN(S) AT THE WIDEST POINT

VITALITY:

A MEASURE OF PHYSIOLOGICAL CONDITION WHEREBY D = DEAD, MD = MORIBUND, P = POOR, M = MODERATE, G = GOOD

MANAGEMENT:

SUFFIXES: (M) = FOR GENERAL ARBORICULTURAL OR SILVICULTURAL MANAGEMENT; (S) = TO REMOVE OR REDUCE THE RISK OF DIRECT DAMAGE TO A FIXED STRUCTURE BY MEANS OF CIRCUMFERENTIAL ROOT, STEM OR BRANCH GROWTH; (I) = TO ENABLE THE TREE(S) TO BE INSPECTED

FURTHER FOR RISK ASSESSMENT PURPOSES

TARGET RANGE:

HIGHEST VALUE TARGET THAT THE MOST SIGNIFICANT PART LIKELY TO FAIL COULD STRIKE. RANGES 1-6. 1 = HIGH, 6 = LOW VALUE/OCCUPANCY

RISK ASSESSMENT DESCRIPTION:

DESCRIPTION OF PART IDENTIFIED AS MOST LIKELY TO FAIL AND ASSOCIATED TARGET, ASSESSED IN ACCORDANCE WITH QTRA SYSTEM

SIZE RANGE:

SIZE CATEGORY OF MOST SIGNIFICANT PART CONSIDERED LIKELY TO FAIL. - RANGES 1-4 WHEREBY 1 = LARGE, 4 = SMALL, P = PROPERTY

P.O.F:

PROBABILITY OF FAILURE WITHIN 12 MONTHS. RANGES 1-7. 1 = HIGH, 7 = LOW

REDUCED MASS %:

WHERE THE MASS OF A TREE OR BRANCH IS REDUCED BY DEGRADATION THE RISK INDEX IS MULTIPLIED TO REFLECT THE PERCENTAGE OF MASS REDUCTION

RISK INDEX:

E.G. RISK INDEX 20 = RISK OF SIGNIFICANT HARM 1 IN 20,000. AN ADDITIONAL FIGURE, IN BRACKETS, MAY BE SUFFIXED 'T' REPRESENTING THE RATE OF MULTIPLE OCCUPATION OVER THE YEAR, E.G. 10(10T) REPRESENTS A RISK OF HARM 1/10,000 TO 10

OCCUPANTS OR AN EQUIVALENT MONETARY VALUE. SEE QTRA PRACTICE NOTE FOR MORE INFORMATION REGARDING COLOURS USED TO SIGNIFY RISK INDEX

WORK PRIORITY:

H (HIGH) = TREE WORKS TO BE GIVEN IMMEDIATE CONSIDERATION. M (MODERATE) = TREE WORKS TO BE CARRIED OUT WITHIN 12 MONTHS OF SURVEY (TIMING MAY BE SPECIFIED IN MANAGEMENT RECOMMENDATIONS). L (LOW) = TREE WORKS THAT ARE NOT

CONSIDERED ESSENTIAL FOR RISK MANAGEMENT PURPOSES, BUT ARE RECOMMENDED IN ACCORDANCE WITH PRUDENT ARBORICULTURAL MANAGEMENT (TO BE REVIEWED IN 12 MONTHS, OR SPECIFIED TIME, IF APPLICABLE). N/A = NOT APPLICABLE

Site: Throstle Croft, Saccary Lane, Mellor, Lancashire, BB1 9DW

Client: Graham Hoare

Brief: Carry out an individual tree survey within area identified by client, report on projected risk posed to persons and property, and make management recommendations where appropriate

Surveyor: Joseph Lambert BSc(Hons) FdSc MARborA

Survey Date: 2 September 2020

Viewing Conditions: Overcast with prolonged heavy rain

Job Reference: BTC2059

Page: 2 of 8

No.	Species	Age	Height (m)	Stem Diam. (mm)	Crown Spread (m)	Vitality	Comments	Management Recommendations	Risk Assessment Description (Part/Target)	Target	Size	P.O.F	Reduced Mass %	Risk Index	Work Priority
T3	Copper Beech	M	17.5	630	14	G	<ul style="list-style-type: none"> Located immediately adjacent to tree T2 with canopies in very close proximity. Largely occluded historic stem wound to north between ground level and approximately 1.8m, with no evident significant decay. Slight lift in ground to west indicating past movement in soil, although no fresh indications of recent movement and no gap evident between canopy of this tree and neighbouring tree T2. Stem bifurcates at a height of approximately 2.5m with wide union. Canopy highly biased to north-east towards house and in contact with ground in lawn area. 	<ul style="list-style-type: none"> Tree contractor to prune tree to obtain a ground clearance of approximately 2.5m over lawn (M). Tree consultant to monitor tree for future signs of rootplate movement as a component of future cyclical inspections. 	<p>P = Deadwood up to approximately 80mm diameter. T = Persons using garden area adjacent and below tree canopy.</p>	3	4	2	50%	1M	M
T4	Common Holly	M	11	2x250 (ts)	10	M	<ul style="list-style-type: none"> Twin stemmed from a height of approximately 1m. Evidently previously topped at a height of approximately 3m with multiple stems of approximately 150mm diameter now arising from this point. Canopy conflicting with and suppressed by neighbouring Beech tree T3 to south, and partially so by Oak tree T5 to north. Stem arising to north-west of approximately 150mm diameter from a height of approximately 3m towards lane has a large gap between itself and remaining canopy indicating progressive subsidence of stem. Canopy low and encroaching onto lawn to east. 	<ul style="list-style-type: none"> Tree contractor to prune tree to reduce to a height of approximately 3m and reduce remaining foliage by approximately 2m on east side to remove stems with progressive subsidence and those conflicting with canopy of Beech T3 and to provide clearance to lawn (M). NB: Projected tree can be maintained at low level with surrounding shrubs as screening to garden and property. 	<p>P = Stem of approximately 150mm diameter at a height of approximately 3m. T = Vehicles and occupants using adjacent road to west.</p>	3	3	3	N/A	500 K	M
T5	Common Oak	EM	15	430	12	G	<ul style="list-style-type: none"> Large amount of deadwood up to approximately 120mm diameter in inner canopy over road. 	<ul style="list-style-type: none"> Tree contractor to prune tree to remove deadwood >50mm diameter overhanging adjacent road (M). 	<p>P = Deadwood up to approximately 120mm diameter. T = Vehicles and occupants using adjacent road below tree canopy.</p>	3	3	2	50%	100 K	M

Site: Throstle Croft, Saccary Lane, Mellor, Lancashire, BB1 9DW

Client: Graham Hoare

Brief: Carry out an individual tree survey within area identified by client, report on projected risk posed to persons and property, and make management recommendations where appropriate

Surveyor: Joseph Lambert BSc(Hons) FdSc MARborA

Survey Date: 2 September 2020

Viewing Conditions: Overcast with prolonged heavy rain

Job Reference: BTC2059

Page: 3 of 8

No.	Species	Age	Height (m)	Stem Diam. (mm)	Crown Spread (m)	Vitality	Comments	Management Recommendations	Risk Assessment Description (Part/Target)	Target	Size	P.O.F	Reduced Mass %	Risk Index	Work Priority
T6	Copper Beech	EM	14	490	16	G	<ul style="list-style-type: none"> ■ Moderate stem lean to east from ground level. ■ Exposed roots on surface in ground to west and partially raised ground indicating partial previous historic rootplate failure, although tree has evidently stabilised. ■ Stem bifurcates at a height of approximately 2.5m with a moderately wide union. ■ Stem arising to east towards property becomes dominant in height. ■ Canopy very low over lawn area and overhanging roof of neighbouring residential property by approximately 2m. ■ Tree canopy in close proximity to roof and wall of adjacent residential property. ■ Canopy moderately biased to south-east. 	<ul style="list-style-type: none"> ■ Tree contractor to prune tree to reduce canopy to south-east to obtain a clearance of approximately 2.5m from adjacent residential property and to obtain a clearance of approximately 2.5m over lawn (M). ■ Tree consultant to monitor tree for future signs of rootplate movement as a component of future cyclical inspections. 	<p>P = Whole stem at ground level. T = Residential property and occupants to east.</p>	3	P	4	N/A	300 K	M
T7	Sycamore	EM	13	400	10	M	<ul style="list-style-type: none"> ■ Severe stem lean to south-east and heave in soil to north-west of stem, thereby indicating past partial rootplate failure. ■ Gap of approximately 50mm between exposed root on west side and stem, thereby indicating historic primary root failure. ■ Canopy showing a moderate reduction in vitality with small leaves and short annual shoot extension. ■ Canopy suppressed by larger Oak to south-east. 	<ul style="list-style-type: none"> ■ Tree contractor to remove tree due to identified increased risk of main stem failure and subsequent unacceptable risk of harm to persons. 	<p>P = Whole stem at ground level. T = Persons using garden area adjacent to and below tree.</p>	3	2	2	N/A	10K	H

Site: Throstle Croft, Saccary Lane, Mellor, Lancashire, BB1 9DW

Client: Graham Hoare

Brief: Carry out an individual tree survey within area identified by client, report on projected risk posed to persons and property, and make management recommendations where appropriate

Surveyor: Joseph Lambert BSc(Hons) FdSc MARborA

Survey Date: 2 September 2020

Viewing Conditions: Overcast with prolonged heavy rain

Job Reference: BTC2059

Page: 4 of 8

No.	Species	Age	Height (m)	Stem Diam. (mm)	Crown Spread (m)	Vitality	Comments	Management Recommendations	Risk Assessment Description (Part/Target)	Target	Size	P.O.F	Reduced Mass %	Risk Index	Work Priority
T8	Sycamore	M	21	500	14	G	<ul style="list-style-type: none"> Moderately dense ivy cover to stem and branches which impeded inspection. Stem bifurcates at a height of approximately 2.5m with moderately wide union. Moderately large amount of deadwood up to approximately 120mm diameter and 4m length over garden area. 	<ul style="list-style-type: none"> Tree contractor to sever ivy around stem circumference from ground level to a height of approximately 2m, and remove ivy section between (I). NB: Client to inform tree consultant on completion of works and dieback of ivy. Tree consultant to re-inspect stem and buttresses following removal and dieback of ivy. NBB: QTRA index to be re-calculated following re-inspection. Tree contractor to remove deadwood >75mm diameter (M). 	P = Deadwood up to approximately 120mm diameter. T = Persons using garden area adjacent to and below tree	3	3	2	50%	100 K	H
T9	Common Lime	M	18	600	12	M	<ul style="list-style-type: none"> Dense basal growth and number of well-established adventitious shoots up to approximately 120mm diameter from ground level, which significantly impeded inspection. Moderately dense ivy cover further impeded inspection. Stem bifurcates at a height of approximately 2m. Upper canopy showing a moderate reduction in vitality, although it is noted that surrounding trees partially restricted view of upper canopy. Moderate amount of deadwood up to approximately 100mm diameter in inner canopy. 	<ul style="list-style-type: none"> Tree contractor to sever ivy around stem circumference from ground level to a height of approximately 6m, and remove ivy section between, and to prune tree to remove basal growth between ground level and a height of approximately 6m. NB: Client to inform tree consultant on completion of works and dieback of ivy. Tree consultant to re-inspect stem and buttresses following removal and dieback of ivy and removal of basal growth. NBB: QTRA index to be re-calculated following re-inspection. 	P = Deadwood up to approximately 100mm diameter. T = Persons using garden area adjacent to and below tree	3	4	3	50%	<1M	H
T10	Silver Birch	M	16	440	10	M	<ul style="list-style-type: none"> Suppressed by larger neighbouring Oak tree T11. Partially occluded basal wound of approximately 80mm width and 300mm height on east side of stem. 	<ul style="list-style-type: none"> Tree consultant to monitor basal wound for signs of decay as a component of future cyclical inspections. 	P = Deadwood up to approximately 50mm diameter. T = Persons using adjacent bridleway to east.	3	4	3	50%	<1M	L

Site: Throstle Croft, Saccary Lane, Mellor, Lancashire, BB1 9DW

Client: Graham Hoare

Brief: Carry out an individual tree survey within area identified by client, report on projected risk posed to persons and property, and make management recommendations where appropriate

Surveyor: Joseph Lambert BSc(Hons) FdSc MARborA

Survey Date: 2 September 2020

Viewing Conditions: Overcast with prolonged heavy rain

Job Reference: BTC2059

Page: 5 of 8

No.	Species	Age	Height (m)	Stem Diam. (mm)	Crown Spread (m)	Vitality	Comments	Management Recommendations	Risk Assessment Description (Part/Target)	Target	Size	P.O.F	Reduced Mass %	Risk Index	Work Priority
T11	Common Oak	M	23.5	600	16	M	<ul style="list-style-type: none"> Lowest branch of approximately 80mm diameter arising to east at a height of approximately 5.5m is dead at its end over driveway and bridleway. Moderate amount of deadwood within inner canopy up to approximately 80mm diameter. Canopy low over lawn to south-west. 	<ul style="list-style-type: none"> Tree contractor to prune tree to remove deadwood >50mm diameter over bridleway (M) and to obtain a ground clearance of approximately 2.5m over lawn (M). 	P = Deadwood up to approximately 150mm diameter. T = Persons using adjacent bridleway below tree canopy.	3	3	2	50%	100 K	M
T12	Silver Birch	M	20	340	10	M	<ul style="list-style-type: none"> Canopy moderately biased to west. Main stem bifurcates at a height of approximately 4m with wide union. Canopy low over lawn. 	<ul style="list-style-type: none"> Tree contractor to prune tree to obtain a ground clearance of approximately 2.5m over lawn (M). 	P = Deadwood up to approximately 75mm diameter. T = Persons using garden area below and adjacent to tree canopy.	3	4	3	50%	<1M	L
T13	Common Beech	M	23.5	630	14	G	<ul style="list-style-type: none"> Located adjacent to west of low voltage overhead power lines and moderate use driveway/bridleway. Number of partly occluded wounds and areas of bark dysfunction between ground level and a height of approximately 1.2m; of approximately 350mm width between 3m and 4.5m; of approximately 350mm width between 7m and 9m, and with further area of dysfunctional bark above to a height of approximately 11m height. Evident decay visible in upper wounds, however foliated canopy partially restricted detailed inspection. Considered to have an increased risk of upper stem failure from ground level inspection. 	<ul style="list-style-type: none"> Tree contractor to remove tree due to identified increased risk of upper stem failure and unacceptable risk of damage to property. 	P = Stem of approximately 400mm diameter at a height of approximately 11m. T = Overhead power and telephone cables and adjacent garage.	3	P	2	N/A	3K	H
T14	Common Lime	M	23	520	12	G	<ul style="list-style-type: none"> Stem bifurcates at a height of approximately 3m with moderately tight union. Light epicormic growth between ground level and a height of approximately 3m. Canopy low over adjacent lawn. 	<ul style="list-style-type: none"> Tree contractor to prune tree to remove epicormic growth to a height of approximately 3m to prevent restriction to future detailed inspections (I). Tree contractor to prune tree to obtain a ground clearance of approximately 2.5m (M). 	P = Deadwood up to approximately 60mm diameter. T = Persons using garden below tree canopy.	4	4	2	25%	<1M	M

Site: Throstle Croft, Saccary Lane, Mellor, Lancashire, BB1 9DW

Client: Graham Hoare

Brief: Carry out an individual tree survey within area identified by client, report on projected risk posed to persons and property, and make management recommendations where appropriate

Surveyor: Joseph Lambert BSc(Hons) FdSc MARborA

Survey Date: 2 September 2020

Viewing Conditions: Overcast with prolonged heavy rain

Job Reference: BTC2059

Page: 6 of 8

No.	Species	Age	Height (m)	Stem Diam. (mm)	Crown Spread (m)	Vitality	Comments	Management Recommendations	Risk Assessment Description (Part/Target)	Target	Size	P.O.F	Reduced Mass %	Risk Index	Work Priority
T15	Wild Cherry	M	20	400	10	M	<ul style="list-style-type: none"> Located in garden border with canopy over garden border area. Very dense ivy cover, which significantly impeded inspection of upper stem and is now becoming dominant in canopy. 	<ul style="list-style-type: none"> Tree contractor to sever ivy at ground level around entire stem circumference and a height of approximately 2m and remove section in between in order to prevent dominance in canopy and facilitate future inspections (M). 	P = Deadwood up to approximately 75mm diameter. T = Persons using garden area below tree canopy.	4	4	2	50%	<1M	M
T16	Common Lime	M	20	430	12	G	<ul style="list-style-type: none"> Stem bifurcates at a height of approximately 3.5m. No significant defects visible at time of survey. 	<ul style="list-style-type: none"> 	P = Deadwood up to approximately 60mm diameter. T = Persons using adjacent driveway.	3	4	2	25%	<1M	N/A
T17	Swedish Whitebeam	M	12	400	12	M	<ul style="list-style-type: none"> Canopy suppressed by larger Ash tree above. Indications of moderate basal hollowing when sounded with nylon mallet, although no visible cavities or decay fungal fruiting bodies at time of survey, and tree occupies a sheltered location within wider group of trees. 	<ul style="list-style-type: none"> Tree consultant to monitor tree's structural and physiological condition as a component of future cyclical inspections. 	P = Main stem at ground level. T = Persons using driveway adjacent to tree.	3	2	4	N/A	1M	L
T18	Common Oak	M	22	460	14	M	<ul style="list-style-type: none"> Located within neighbouring garden to south, and subsequently not accessed to inspect in detail. Significant stem lean to north-west from a height of approximately 5m. Canopy highly biased to north-west over access driveway to Throstle Croft. Several evident longitudinal wounds with staining at base from a height of approximately 1.5m to 5m indicating partial torsional failure of stem. 	<ul style="list-style-type: none"> Client to inform tree owner of findings of report. Tree owner to instruct tree contractor to remove tree due to incipient signs of failure and subsequent unacceptable risk of harm to persons. 	P = Main stem at a height of approximately 1.5m. T = Persons using access driveway to Throstle Croft to north-west.	3	1	1	N/A	400	H
G1	6no. Silver Birch, 2no. Oak, 1no. Hornbeam	Y-EM	≤ 15	≤ 300	≤ 11	G	<ul style="list-style-type: none"> Moderately to closely spaced group located on raised earth mound. Hornbeam to north-west has significant animal damage to bark between ground level and a height of approximately 3m to main stem and primary branches animal damage. Moderate amount of deadwood up to approximately 50mm diameter within canopies. Stem of Cherry to north-east of group bifurcates at a height of approximately 1m with very tight union. 	<ul style="list-style-type: none"> 	P = Deadwood up to approximately 50mm diameter. T = Persons using garden area below.	4	4	2	50%	<1M	N/A

Site: Throstle Croft, Saccary Lane, Mellor, Lancashire, BB1 9DW

Client: Graham Hoare

Brief: Carry out an individual tree survey within area identified by client, report on projected risk posed to persons and property, and make management recommendations where appropriate

Surveyor: Joseph Lambert BSc(Hons) FdSc MARborA

Survey Date: 2 September 2020

Viewing Conditions: Overcast with prolonged heavy rain

Job Reference: BTC2059

Page: 7 of 8

No.	Species	Age	Height (m)	Stem Diam. (mm)	Crown Spread (m)	Vitality	Comments	Management Recommendations	Risk Assessment Description (Part/Target)	Target	Size	P.O.F	Reduced Mass %	Risk Index	Work Priority
G2	1no. Common Holly, 1no. Silver Birch	SM-EM	≤ 10	≤ 290	≤ 7	G	■ Ivy becoming moderately dense in top of canopy of Holly.	■ Tree contractor to sever ivy around stem circumference from ground level to a height of approximately 2m, and remove ivy section between to prevent dominance within canopy (M).	P = Deadwood up to approximately 50mm diameter. T = Vehicles and occupants using road.	3	4	3	50%	<1M	M
G3	4no. Common Holly, 1no. Acer sp. 1no. Birch, 1no. Damson, 1no. Kanzan Cherry, 1no. Sycamore	EM-M	≤ 16	≤ 350	≤ 12	M-G	■ Closely spaced group in north-east corner of garden within shrub border. ■ Sycamore stem has moderate ivy cover to stem. ■ Stem of Cherry trifurcates at ground level with very tight unions and included bark. ■ Two dead stems up to approximately 180mm diameter within Hollies to north-east, arising from a height of approximately 0.5m over adjacent road. ■ Holly to centre-north has partially occluded wound of approximately 250mm diameter on south side at a height of approximately 1m.	■ Tree contractor to prune Hollies to remove dead stems over road due to identified increased risk of failure and subsequent unacceptable risk of harm to persons. ■ Tree contractor to sever ivy around Sycamore's stem circumference from ground level to a height of approximately 2m, and remove ivy section between to prevent dominance within canopy (M).	P = Dead Holly stems of approximately 180mm diameter. T = Vehicles and occupant using adjacent road.	3	3	1	N/A	5K	H
G4	4no. Sycamore	M	≤ 22	≤ 530	≤ 12	M-G	■ Moderately spaced group. ■ Moderate ivy cover to stems, which impeded inspection. ■ Moderate amount of deadwood up to approximately 120mm diameter within canopies, with several pieces extending to east over bridleway.	■ Tree contractor to sever ivy around stem circumferences from ground level to a height of approximately 2m, and remove ivy section between (I). NB: Client to inform tree consultant on completion of works and dieback of ivy. ■ Tree consultant to re-inspect stems and buttresses following removal and dieback of ivy. NBB: QTRA index to be re-calculated following re-inspection. ■ Tree contractor to prune trees to remove deadwood >75mm diameter over bridleway (M).	P = Deadwood up to approximately 120mm diameter. T = Persons using adjacent bridleway below trees' canopies.	3	3	2	50%	100 K	M

Site: Throstle Croft, Saccary Lane, Mellor, Lancashire, BB1 9DW

Client: Graham Hoare

Brief: Carry out an individual tree survey within area identified by client, report on projected risk posed to persons and property, and make management recommendations where appropriate

Surveyor: Joseph Lambert BSc(Hons) FdSc MARborA


Survey Date: 2 September 2020

Viewing Conditions: Overcast with prolonged heavy rain

Job Reference: BTC2059

Page: 8 of 8

No.	Species	Age	Height (m)	Stem Diam. (mm)	Crown Spread (m)	Vitality	Comments	Management Recommendations	Risk Assessment Description (Part/Target)	Target	Size	P.O.F	Reduced Mass %	Risk Index	Work Priority
G5	3no. Common Lime, 1no. Sycamore	EM-M	≤ 21	≤ 610	≤ 14	G	<ul style="list-style-type: none"> Moderately spaced linear group. Limes have moderate basal growth, established adventitious shoots to up to 120mm diameter, and light ivy cover which impeded inspection. Lime tree to centre has two largely occluded wounds between ground level and a height of approximately 1.2m light ivy cover bases. Moderate amount of deadwood within canopy up to approximately 75mm diameter to east over bridleway. Canopies low to east over neighbouring driveway and bridleway, and are in contact with garage roof and greenhouse roof to west. 	<ul style="list-style-type: none"> Tree contractor to prune Limes to remove basal growth between ground level and a height of approximately 6m. NB: Client to inform tree consultant on completion of works (!). Tree consultant to re-inspect stems and buttresses following removal of basal growth. NBB: QTRA index to be re-calculated following re-inspection. Tree contractor to prune canopies to obtain a 4m ground clearance over driveway to east and a 1.5m clearance from garage and greenhouse roof (M). 	P = Deadwood up to approximately 75mm diameter. T = Persons using bridleway to east.	3	4	2	25%	<1M	H
G6	4no. Common Ash	M	≤ 21	≤ 380	≤ 16	M	<ul style="list-style-type: none"> Canopies showing minor twig dieback due to colonisation by Ash Dieback Disease. Tree of approximately 260mm diameter to west of group as severely attenuated form with canopy highly biased west, and is showing a severe reduction in vitality. Stem is rubbing and crossing upper canopy of neighbouring Lime tree T16 to west at a height of approximately 15m. Deadwood of approximately 150mm diameter over garden in tree to south. 	<ul style="list-style-type: none"> Tree contractor to remove tree to west that is conflicting with Lime due to poor form and limited future potential (M). Tree consultant to monitor progression of Ash Dieback Disease as a component of future cyclical inspections. 	P = Deadwood up to approximately 150mm diameter. T = Persons using garden area below.	4	3	3	N/A	<1M	L



T = Individual Tree, **G** = Group of Trees

- 📍 (Red) = Tree/Group with Risk of Harm of 1/1,000 or greater
- 📍 (Orange) = Tree/Group with Risk of Harm between 1/1,000 and 1/10,000
- 📍 (Yellow) = Tree/Group with Risk of Harm between 1/10,000 and 1/1,000,000
- 📍 (Green) = Tree/Group with Risk of Harm less than 1/1,000,000

* See QTRA Methodology Overview and Application in Management Decisions Section of Report for details regarding Risk of Harm

Site: Throstle Croft, Saccary Lane,
Mellor, BB1 9DW

Job No.: BTC2059

Scale: Not to Scale


Paper Size (for printing): A3

Date: September 2020

TREE SURVEY PLAN (Overview)

Bowland 
Tree Consultancy Ltd

e: Info@bowlandtreeconsultancy.co.uk
t: 01772 437150



TREE SURVEY PLAN

(north)

Bowland 
Tree Consultancy Ltd

e: Info@bowlandtreeconsultancy.co.uk
t: 01772 437150



DISCLAIMER

Survey Limitations: Unless otherwise stated all trees are viewed from ground level using non-invasive techniques. The disclosure of hidden crown and stem defects, in particular where they may be above a reachable height or where trees are ivy clad or in areas of ground vegetation, cannot therefore be expected. All obvious defects, however, are reported. Where the QTRA Risk Index is calculated as Tolerable or Broadly Acceptable, but the tree(s) have not been adequately inspected (e.g. due to the presence of ivy and/or ground vegetation which impeded the inspection), then it is essential to follow the recommendations made in the Management Recommendations column and to have the applicable tree(s) re-inspected as recommended.

Detailed tree safety appraisals are only carried out under specific written instructions. Comments upon evident tree safety relate to the condition of said tree at the time of the survey only. The level of detail of the survey is as per the brief detailed on the Tree Survey Schedule and as per the specifics set out in the associated fee estimate for the project.

Unless otherwise stated all trees should be re-inspected annually in order to appraise their on-going mechanical integrity and physiological condition. It should, however, be recognised that tree condition is subject to change, for example due to the effects of disease, decay, high winds, development works, etc. Changes in land use or site conditions (e.g. development that increases access frequency) and the occurrence of severe weather incidents are also significant considerations with regards tree structural integrity and trees should therefore be re-assessed in the context of such changes and/or incidents and inspected at intervals relative to identified and varying site conditions and associated risks.

Where trees are located wholly or partially on neighbouring private third-party land then said land is not accessed and our inspection is therefore restricted to what can reasonably be seen from within the site. Any subsequent comments and judgments made in respect of such trees are based on these restrictions and are our preliminary opinion only. Recommendations for works to neighbouring third-party trees are only made where a potentially unacceptable risk to persons and/or property has been identified during our survey. Where significant structural defects of third-party trees are identified and associated management works are considered essential to negate any risk of harm and/or damage then we will first attempt to inform the site occupier of the issues and, if not possible, then inform the relevant Council. Where a more detailed assessment is considered necessary then appropriate recommendations are set out in the Tree Survey Schedule.

The potential influence of trees upon existing or proposed buildings or other structures, resulting from the effects of their roots abstracting water from shrinkable load-bearing soils, is not considered herein.

Copyright & Non-Disclosure Notice: The content and layout of this report are subject to copyright owned by Bowland Tree Consultancy Ltd, save to the extent that copyright has been legally assigned to us by another party or is used by Bowland Tree Consultancy Ltd under license. This report may not be copied or used without our prior written agreement for any purpose other than those indicated.

Third Parties: Any disclosure of this document to a third party is subject to this disclaimer. The report was prepared by Bowland Tree Consultancy Ltd at the instruction of and for use by our client, as named. This report does not in any way constitute advice to any third party who is able to access it by any means. Bowland Tree Consultancy Ltd excludes to the fullest extent lawfully permitted all liability whatsoever for any loss or damage arising from reliance on the contents of this report.

Statutory Tree Protection: It is the client's responsibility to check for the presence of any statutory tree protection measures, such as the site's location within a Conservation Area and/or the presence of any Tree Preservation Orders, directly with the applicable Council's planning department prior to scheduling or carrying out any tree works. In turn, it is also the client's responsibility to check for the need for a felling licence with the Forestry Commission prior to scheduling or carrying out any tree works. Bowland Tree Consultancy Ltd cannot be held responsible for any decisions made by the client to prune or remove trees where any such statutory protection exists.



Quantified Tree Risk Assessment
Simply Balancing Risks With Benefits



Quantified Tree Risk Assessment
PRACTICE NOTE

VERSION 5

Quantified Tree Risk Assessment Practice Note

"When you can measure what you are speaking about, and express it in numbers, you know something about it; but when you cannot measure it, when you cannot express it in numbers, your knowledge is of a meagre and unsatisfactory kind"

William Thomson, Lord Kelvin, Popular Lectures and Addresses [1891-1894]

1. INTRODUCTION

Every day we encounter risks in all of our activities, and the way we manage those risks is to make choices. We weigh up the costs and benefits of the risk to determine whether it is acceptable, unacceptable, or tolerable. For example, if you want to travel by car you must accept that even with all the extensive risk control measures, such as seat-belts, speed limits, airbags, and crash barriers, there is still a significant risk of death. This is an everyday risk that is taken for granted and tolerated by millions of people in return for the benefits of convenient travel. Managing trees should take a similarly balanced approach.

A risk from falling trees exists only if there is both potential for tree failure and potential for harm to result. The job of the risk assessor is to consider the likelihood and consequences of tree failure. The outcome of this assessment can then inform consideration of the risk by the tree manager, who may also be the owner.

Using a comprehensive range of values¹, Quantified Tree Risk Assessment (QTRA) enables the tree assessor to identify and analyse the risk from tree failure in three key stages. 1) to consider land-use in terms of vulnerability to impact and likelihood of occupation, 2) to consider the consequences of an impact, taking account of the size of the tree or branch concerned, and 3) to estimate the probability that the tree or branch will fail onto the land-use in question. Estimating the values of these components, the assessor can use the QTRA manual calculator or software application to calculate an annual Risk of Harm from a particular tree. To inform management decisions, the risks from different hazards can then be both ranked and compared, and considered against broadly acceptable and tolerable levels of risk.

A Proportionate Approach to Risks from Trees

The risks from falling trees are usually very low and high risks will usually be encountered only in areas

with either high levels of human occupation or with valuable property. Where levels of human occupation and value of property are sufficiently low, the assessment of trees for structural weakness will not usually be necessary. Even when land-use indicates that the assessment of trees is appropriate, it is seldom proportionate to assess and evaluate the risk for each individual tree in a population. Often, all that is required is a brief consideration of the trees to identify gross signs of structural weakness or declining health. Doing all that is reasonably practicable does not mean that all trees have to be individually examined on a regular basis (HSE 2013).

The QTRA method enables a range of approaches from the broad assessment of large collections of trees to, where necessary, the detailed assessment of an individual tree.

Risk of Harm

The QTRA output is termed the Risk of Harm and is a combined measure of the likelihood and consequences of tree failure, considered against the baseline of a lost human life within the coming year.

ALARP (As Low As Reasonably Practicable)

Determining that risks have been reduced to As Low As Reasonably Practicable (HSE 2001) involves an evaluation of both the risk and the sacrifice or cost involved in reducing that risk. If it can be demonstrated that there is gross disproportion between them, the risk being insignificant in relation to the sacrifice or cost, then to reduce the risk further is not 'reasonably practicable'.

Costs and Benefits of Risk Control

Trees confer many benefits to people and the wider environment. When managing any risk, it is essential to maintain a balance between the costs and benefits of risk reduction, which should be considered in the determination of ALARP. It is not only the financial cost of controlling the risk that should be considered, but also the loss of tree-related benefits, and the risk to workers and the public from the risk control measure itself.

¹ See Tables 1, 2 & 3.

When considering risks from falling trees, the cost of risk control will usually be too high when it is clearly 'disproportionate' to the reduction in risk. In the context of QTRA, the issue of 'gross disproportion'², where decisions are heavily biased in favour of safety, is only likely to be considered where there are risks of 1/10 000 or greater.

Acceptable and Tolerable Risks

The Tolerability of Risk framework (ToR) (HSE 2001) is a widely accepted approach to reaching decisions on whether risks are broadly acceptable, unacceptable, or tolerable. Graphically represented in Figure 1, ToR can be summarised as having a Broadly Acceptable Region where the upper limit is an annual risk of death 1/1 000 000, an Unacceptable Region for which the lower limit is 1/1 000, and between these a Tolerable Region within which the tolerability of a risk will be dependent upon the costs and benefits of risk reduction. In the Tolerable Region, we must ask whether the benefits of risk control are sufficient to justify their cost.

In respect of trees, some risks cross the Broadly Acceptable 1/1 000 000 boundary, but remain tolerable. This is because any further reduction would involve a disproportionate cost in terms of the lost environmental, visual, and other benefits, in addition to the financial cost of controlling the risk.




Figure 1. Adapted from the Tolerability of Risk framework (HSE 2001).

Value of Statistical Life

The Value of Statistical Life (VOSL), is a widely applied risk management device, which uses the value of a hypothetical life to guide the proportionate allocation of resources to risk reduction. In the UK,

this value is currently in the region of £2 000 000, and this is the value adopted in the QTRA method.

In QTRA, placing a statistical value on a human life has two particular uses. Firstly, QTRA uses VOSL to enable damage to property to be compared with the loss of life, allowing the comparison of risks to people and property. Secondly, the proportionate allocation of financial resources to risk reduction can be informed by VOSL. "A value of statistical life of £1 000 000 is just another way of saying that a reduction in risk of death of 1/100 000 per year has a value of £10 per year" (HSE 1996).

Internationally, there is variation in VOSL, but to provide consistency in QTRA outputs, it is suggested that VOSL of £2 000 000 should be applied internationally. This is ultimately a decision for the tree manager.

2. OWNERSHIP OF RISK

Where many people are exposed to a risk, it is shared between them. Where only one person is exposed, that individual is the recipient of all of the risk and if they have control over it, they are also the owner of the risk. An individual may choose to accept or reject any particular risk to themselves, when that risk is under their control. When risks that are imposed upon others become elevated, societal concern will usually require risk controls, which ultimately are imposed by the courts or government regulators.

Although QTRA outputs might occasionally relate to an individual recipient, this is seldom the case. More often, calculation of the Risk of Harm is based on a cumulative occupation – i.e. the number of people per hour or vehicles per day, without attempting to identify the individuals who share the risk.

Where the risk of harm relates to a specific individual or a known group of people, the risk manager might consider the views of those who are exposed to the risk when making management decisions. Where a risk is imposed on the wider community, the principles set out in the ToR framework can be used as a reasonable approach to determine whether the risk is ALARP.

3. THE QTRA METHOD - VERSION 5

The input values for the three components of the QTRA calculation are set out in broad ranges³ of Target, Size, and Probability of Failure. The assessor

² Discussed further on page 5.

³ See Tables 1, 2 & 3.

estimates values for these three components and inputs them on either the manual calculator or software application to calculate the Risk of Harm.

Assessing Land-use (Targets)

The nature of the land-use beneath or adjacent to a tree will usually inform the level and extent of risk assessment to be carried out. In the assessment of Targets, six ranges of value are available. Table 2 sets out these ranges for vehicular frequency, human occupation and the monetary value of damage to property.

Human Occupation

The probability of pedestrian occupation at a particular location is calculated on the basis that an average pedestrian will spend five seconds walking beneath an average tree. For example, ten pedestrians per day, each occupying the Target for five seconds, is a daily occupation of fifty seconds. The total seconds in a day are divided to give a probability of Target occupation ($50/86\,400 = 1/1\,728$). Where a longer occupation is likely, as with a habitable building, outdoor café, or park bench, the period of occupation can be measured, or estimated as a proportion of a given unit of time, e.g. six hours per day ($1/4$). The Target is recorded as a range (Table 2).

Weather Affected Targets

Often the nature of a structural weakness in a tree is such that the probability of failure is greatest during windy weather, while the probability of the site being occupied by people during such weather is often low. This applies particularly to outdoor recreational areas. When estimating human Targets, the risk assessor must answer the question 'in the weather conditions that I expect the likelihood of failure of the tree to be initiated, what is my estimate of human occupation?' Taking this approach, rather than using the average occupation, ensures that the assessor considers the relationship between weather, people, and trees, along with the nature of the average person with their ability to recognise and avoid unnecessary risks.

Vehicles on the Highway

In the case of vehicles, likelihood of occupation may relate to either the falling tree or branch striking the vehicle or the vehicle striking the fallen tree. Both types of impact are influenced by vehicle speed; the faster the vehicle travels the less likely it is to be struck by the falling tree, but the more likely it is to strike a fallen tree. The probability of a vehicle

occupying any particular point in the road is the ratio of the time it is occupied - including a safe stopping distance - to the total time. The average vehicle on a UK road is occupied by 1.6 people (DfT 2010). To account for the substantial protection that the average vehicle provides against most tree impacts and in particular, frontal collisions, QTRA values the substantially protected 1.6 occupants in addition to the value of the vehicle as equivalent to one exposed human life.

Property

Property can be anything that could be damaged by a falling tree, from a dwelling, to livestock, parked car, or fence. When evaluating the exposure of property to tree failure, the QTRA assessment considers the cost of repair or replacement that might result from failure of the tree. Ranges of value are presented in Table 2 and the assessor's estimate need only be sufficient to determine which of the six ranges the cost to select.

In Table 2, the ranges of property value are based on a VOSL of £2 000 000, e.g. where a building with a replacement cost of £20 000 would be valued at 0.01 ($1/100$) of a life (Target Range 2).

When assessing risks in relation to buildings, the Target to be considered might be the building, the occupants, or both. Occupants of a building could be protected from harm by the structure or substantially exposed to the impact from a falling tree if the structure is not sufficiently robust, and this will determine how the assessor categorises the Target.

Multiple Targets

A Target might be constantly occupied by more than one person and QTRA can account for this. For example, if it is projected that the average occupation will be constant by 10 people, the Risk of Harm is calculated in relation to one person constantly occupying the Target before going on to identify that the average occupation is 10 people. This is expressed as Target 1(10T)/1, where 10T represents the Multiple Targets. In respect of property, a Risk of Harm 1(10T)/1 would be equivalent to a risk of losing £20 000 000 as opposed to £2 000 000.

Tree or Branch Size

A small dead branch of less than 25mm diameter is not likely to cause significant harm even in the case of direct contact with a Target, while a falling branch with a diameter greater than 450mm is likely to cause some harm in the event of contact with all but the most robust Target. The QTRA method categorises

Size by the diameter of tree stems and branches (measured beyond any basal taper). An equation derived from weight measurements of trees of different stem diameters is used to produce a data set of comparative weights of trees and branches ranging from 25mm to 600mm diameter, from which Table 1 is compiled. The size of dead branches might be discounted where they have undergone a significant reduction in weight because of degradation and shedding of subordinate branches. This discounting, referred to as 'Reduced Mass',

reflects an estimated reduction in the mass of a dead branch.

Table 1. Size

Size Range	Size of tree or branch	Range of Probability
1	> 450mm (>18") dia.	1/1 - >1/2
2	260mm (10½") dia. - 450mm (18") dia.	1/2 - >1/8.6
3	110mm (4½") dia. - 250mm (10") dia.	1/8.6 - >1/82
4	25mm (1") dia. - 100mm (4") dia.	1/82 - 1/2 500

* Range 1 is based on a diameter of 600mm.

Table 2. Targets

Target Range	Property (repair or replacement cost)	Human (not in vehicles)	Vehicle Traffic (number per day)	Ranges of Value (probability of occupation or fraction of £2 000 000)
1	£2 000 000 - >£200 000	Occupation: Constant – 2.5 hours/day Pedestrians 720/hour – 73/hour & cyclists:	26 000 – 2 700 @ 110kph (68mph) 32 000 – 3 300 @ 80kph (50mph) 47 000 – 4 800 @ 50kph (32mph)	1/1 – >1/10
2	£200 000 - >£20 000	Occupation: 2.4 hours/day – 15 min/day Pedestrians 72/hour – 8/hour & cyclists:	2 600 – 270 @ 110kph (68mph) 3 200 – 330 @ 80kph (50mph) 4 700 – 480 @ 50kph (32mph)	1/10 – >1/100
3	£20 000 - >£2 000	Occupation: 14 min/day – 2 min/day Pedestrians 7/hour – 2/hour & cyclists:	260 – 27 @ 110kph (68mph) 320 – 33 @ 80kph (50mph) 470 – 48 @ 50kph (32mph)	1/100 – >1/1 000
4	£2 000 - >£200	Occupation: 1 min/day – 2 min/week Pedestrians 1/hour – 3/day & cyclists:	26 – 4 @ 110kph (68mph) 32 – 4 @ 80kph (50mph) 47 – 6 @ 50kph (32mph)	1/1 000 – >1/10 000
5	£200 - >£20	Occupation: 1 min/week – 1 min/month Pedestrians 2/day – 2/week & cyclists:	3 – 1 @ 110kph (68mph) 3 – 1 @ 80kph (50mph) 5 – 1 @ 50kph (32mph)	1/10 000 – >1/100 000
6	£20 – £2	Occupation: <1 min/month – 0.5 min/year Pedestrians 1/week – 6/year & cyclists:	None	1/100 000 – 1/1 000 000

Vehicle, pedestrian and property Targets are categorised by their frequency of use or their monetary value. The probability of a vehicle or pedestrian occupying a Target area in Target Range 4 is between the upper and lower limits of 1/1 000 and >1/10 000 (column 5). Using the VOSL £2 000 000, the property repair or replacement value for Target Range 4 is £2 000 - >200.

Probability of Failure

In the QTRA assessment, the probability of tree or branch failure within the coming year is estimated and recorded as a range of value (Ranges 1 – 7, Table 3).

Selecting a Probability of Failure (PoF) Range requires the assessor to compare their assessment of the tree or branch against a benchmark of either a non-compromised tree at Probability of Failure Range 7, or a tree or branch that we expect to fail within the year, which can be described as having a 1/1 probability of failure.

During QTRA training, Registered Users go through a number of field exercises in order to calibrate their estimates of Probability of Failure.

Table 3. Probability of Failure

Probability of Failure Range	Probability
1	1/1 - >1/10
2	1/10 - >1/100
3	1/100 - >1/1 000
4	1/1 000 - >1/10 000
5	1/10 000 - >1/100 000
6	1/100 000 - >1/1 000 000
7	1/1 000 000 - 1/10 000 000

The probability that the tree or branch will fail within the coming year.

The QTRA Calculation

The assessor selects a Range of values for each of the three input components of Target, Size and Probability of Failure. The Ranges are entered on either the manual calculator or software application to calculate a Risk of Harm.

The Risk of Harm is expressed as a probability and is rounded, to one significant figure. Any Risk of Harm that is lower than 1/1 000 000 is represented as <1/1 000 000. As a visual aid, the Risk of Harm is colour coded using the traffic light system illustrated in Table 4 (page 7).

Risk of Harm - Monte Carlo Simulations

The Risk of Harm for all combinations of Target, Size and Probability of Failure Ranges has been calculated using Monte Carlo simulations⁴. The QTRA Risk of Harm is the mean value from each set of Monte Carlo results.

In QTRA Version 5, the Risk of Harm should not be calculated without the manual calculator or software application.

Assessing Groups and Populations of Trees

When assessing populations or groups of trees, the highest risk in the group is quantified and if that risk is tolerable, it follows that risks from the remaining trees will also be tolerable, and further calculations are unnecessary. Where the risk is intolerable, the next highest risk will be quantified, and so on until a tolerable risk is established. This process requires prior knowledge of the tree manager's risk tolerance.

Accuracy of Outputs

The purpose of QTRA is not necessarily to provide high degrees of accuracy, but to provide for the quantification of risks from falling trees in a way that risks are categorised within broad ranges (Table 4).

4. INFORMING MANAGEMENT DECISIONS

Balancing Costs and Benefits of Risk Control

When controlling risks from falling trees, the benefit of reduced risk is obvious, but the costs of risk control are all too often neglected. For every risk reduced there will be costs, and the most obvious of these is the financial cost of implementing the control measure. Frequently overlooked is the transfer of risks to workers and the public who might be directly affected by the removal or pruning of trees. Perhaps

more importantly, most trees confer benefits, the loss of which should be considered as a cost when balancing the costs and benefits of risk control.

When balancing risk management decisions using QTRA, consideration of the benefits from trees will usually be of a very general nature and not require detailed consideration. The tree manager can consider, in simple terms, whether the overall cost of risk control is a proportionate one. Where risks are approaching 1/10 000, this may be a straightforward balancing of cost and benefits. Where risks are 1/10 000 or greater, it will usually be appropriate to implement risk controls unless the costs are grossly disproportionate to the benefits rather than simply disproportionate. In other words, the balance being weighted more on the side of risk control with higher associated costs.

Considering the Value of Trees

It is necessary to consider the benefits provided by trees, but they cannot easily be monetised and it is often difficult to place a value on those attributes such as habitat, shading and visual amenity that might be lost to risk control.

A simple approach to considering the value of a tree asset is suggested here, using the concept of 'average benefits'. When considered against other similar trees, a tree providing 'average benefits' will usually present a range of benefits that are typical for the species, age and situation. Viewed in this way, a tree providing 'average benefits' might appear to be low when compared with particularly important trees – such as in Figure 2, but should nonetheless be sufficient to offset a Risk of Harm of less than 1/10 000. Without having to consider the benefits of risk controls, we might reasonably assume that below 1/10 000, the risk from a tree that provides 'average benefits' is ALARP.

In contrast, if it can be said that the tree provides lower than average benefits because, for example, it is declining and in poor physiological condition, it may be necessary to consider two further elements. Firstly, is the Risk of Harm in the upper part of the Tolerable Region, and secondly, is the Risk of Harm likely to increase before the next review because of an increased Probability of Failure. If both these conditions apply then it might be appropriate to consider the balance of costs and benefits of risk reduction in order to determine whether the risk is ALARP. This balance requires the tree manager to take a view of both the reduction in risk and the costs of that reduction.

⁴ For further information on the Monte Carlo simulation method, refer to http://en.wikipedia.org/wiki/Monte_Carlo_method



Lower Than Average Benefits from Trees

Usually, the benefits provided by a tree will only be significantly reduced below the ‘average benefits’ that are typical for the species, age and situation, if the life of the benefits is likely to be shortened, perhaps because the tree is declining or dead. That is not to say that a disbenefit, such as undesirable shading, lifting of a footpath, or restricting the growth of other trees, should not also be considered in the balance of costs and benefits.

The horse chestnut tree in Figure 3 has recently died, and over the next few years, may provide valuable habitats. However, for this tree species and the relatively fast rate at which its wood decays, the lifetime of these benefits is likely to be limited to only a few years. This tree has an already reduced value that will continue to reduce rapidly over the coming five to ten years at the same time as the Risk of Harm is expected to increase. There will be changes in the benefits provided by the tree as it degrades. Visual qualities are likely to reduce while the decaying wood provides habitats for a range of species, for a short while at least. There are no hard and fast measures of these benefits and it is for the tree manager to decide what is locally important and how it might be balanced with the risks.

Where a risk is within the Tolerable Region and the tree confers lower than average benefits, it might be appropriate to consider implementing risk control while taking account of the financial cost. Here, VOSL can be used to inform a decision on whether the cost of risk control is proportionate. Example 3 below puts this evaluation into a tree management context.

There will be occasions when a tree is of such minimal value and the monetary cost of risk reduction so low that it might be reasonable to

further reduce an already relatively low risk. Conversely, a tree might be of such considerable value that an annual risk of death greater than 1/10 000 would be deemed tolerable.

Occasionally, decisions will be made to retain elevated risks because the benefits from the tree are particularly high or important to stakeholders, and in these situations, it might be appropriate to assess and document the benefits in some detail. If detailed assessment of benefits is required, there are several methodologies and sources of information (Forest Research 2010).



Delegating Risk Management Decisions

Understanding of the costs with which risk reduction is balanced can be informed by the risk assessor’s knowledge, experience and on-site observations, but the risk management decisions should be made by the tree manager. That is not to say that the tree manager should review and agree every risk control measure, but when delegating decisions to surveyors and other staff or advisors, tree managers should set out in a policy, statement or contract, the principles and perhaps thresholds to which trees and their associated risks will ordinarily be managed.

Based on the tree manager accepting the principles set out in the QTRA Practice Note and or any other specific instructions, the risk assessor can take account of the cost/benefit balance and for most

situations will be able to determine whether the risk is ALARP when providing management recommendations.

Table 4. QTRA Advisory Risk Thresholds

Thresholds	Description	Action
1/1,000	<p>Unacceptable Risks will not ordinarily be tolerated</p>	<ul style="list-style-type: none"> Control the risk
1/10 000	<p>Unacceptable (where imposed on others) Risks will not ordinarily be tolerated</p>	<ul style="list-style-type: none"> Control the risk Review the risk
	<p>Tolerable (by agreement) Risks may be tolerated if those exposed to the risk accept it, or the tree has exceptional value</p>	<ul style="list-style-type: none"> Control the risk unless there is broad stakeholder agreement to tolerate it, or the tree has exceptional value Review the risk
1/1 000 000	<p>Tolerable (where imposed on others) Risks are tolerable if ALARP</p>	<ul style="list-style-type: none"> Assess costs and benefits of risk control Control the risk only where a significant benefit might be achieved at reasonable cost Review the risk
	<p>Broadly Acceptable Risk is already ALARP</p>	<ul style="list-style-type: none"> No action currently required Review the risk

QTRA Informative Risk Thresholds

The QTRA advisory thresholds in Table 4 are proposed as a reasonable approach to balancing safety from falling trees with the costs of risk reduction. This approach takes account of the widely applied principles of ALARP and ToR, but does not dictate how these principles should be applied. While the thresholds can be the foundation of a robust policy for tree risk management, tree managers should make decisions based on their own situation, values and resources. Importantly, to enable tree assessors to provide appropriate management guidance, it is helpful for them to have some understanding of the tree owner's management preferences prior to assessing the trees.

A Risk of Harm that is less than 1/1 000 000 is Broadly Acceptable and is already ALARP. A Risk of Harm 1/1 000 or greater is unacceptable and will not ordinarily be tolerated. Between these two values, the Risk of Harm is in the Tolerable Region of ToR and will be tolerable if it is ALARP. In the Tolerable

Region, management decisions are informed by consideration of the costs and benefits of risk control, including the nature and extent of those benefits provided by trees, which would be lost to risk control measures.

For the purpose of managing risks from falling trees, the Tolerable Region can be further broken down into two sections. From 1/1 000 000 to less than 1/10 000, the Risk of Harm will usually be tolerable providing that the tree confers 'average benefits' as discussed above. As the Risk of Harm approaches 1/10 000 it will be necessary for the tree manager to consider in more detail the benefits provided by the tree and the overall cost of mitigating the risk.

A Risk of Harm in the Tolerable Region but 1/10 000 or greater will not usually be tolerable where it is imposed on others, such as the public, and if retained, will require a more detailed consideration of ALARP. In exceptional circumstances a tree owner might choose to retain a Risk of Harm that is 1/10 000 or greater. Such a decision might be based on the agreement of those who are exposed to the risk, or perhaps that the tree is of great importance. In these circumstances, the prudent tree manager will consult with the appropriate stakeholders whenever possible.

5. EXAMPLE QTRA CALCULATIONS AND RISK MANAGEMENT DECISIONS

Below are three examples of QTRA calculations and application of the QTRA Advisory Thresholds.

Example 1.

Target	Size	Probability of Failure	Risk of Harm
Range	6	x 1 x	= <1/1 000 000

Example 1 is the assessment of a large (Size 1), unstable tree with a probability of failure of between 1/100 and >1/1 000 (PoF 3). The Target is a footpath with less than one pedestrian passing the tree each week (Target 6). The Risk of Harm is calculated as less than 1/1 000 000 (green). This is an example of where the Target is so low consideration of the structural condition of even a large tree would not usually be necessary.

Example 2.

Target	Size	Probability of Failure	Risk of Harm
Range	1 x 4	x 3	= 1(2T)/50 000

In Example 2, a recently dead branch (Size 4) overhangs a busy urban high street that is on average occupied constantly by two people, and here Multiple Target occupation is considered.

Having an average occupancy of two people, the Risk of Harm 1(2T)/50 000 (yellow) represents a twofold increase in the magnitude of the consequence and is therefore equivalent to a Risk of Harm 1/20 000 (yellow). This risk does not exceed 1/10 000, but being a dead branch at the upper end of the Tolerable Region it is appropriate to consider the balance of costs and benefits of risk control. Dead branches can be expected to degrade over time with the probability of failure increasing as a result. Because it is dead, some of the usual benefits from the branch have been lost and it will be appropriate to consider whether the financial cost of risk control would be proportionate.

Example 3.

Target	Size	Probability of Failure	Risk of Harm
Range	3 x 3	x 3	= 1/500 000

In Example 3, a 200mm diameter defective branch overhangs a country road along which travel between 470 and 48 vehicles each day at an average speed of 50kph (32mph) (Target Range 3). The branch is split and is assessed as having a probability of failure for the coming year of between 1/100 and 1/1 000 (PoF Range 3). The Risk of Harm is calculated as 1/500 000 (yellow) and it needs to be considered whether the risk is ALARP. The cost of removing the branch and reducing the risk to Broadly Acceptable (1/1 000 000) is estimated at £350. To establish whether this is a proportionate cost of risk control, the following equation is applied. £2 000 000 (VOSL) x 1/500 000 = £4 indicating that the projected cost of £350 would be disproportionate to the benefit. Taking account of the financial cost, risk transfer to arborists and passers-by, the cost could be described as being grossly disproportionate, even if accrued benefits over say ten years were taken into account.

References

DfT. 2000. Highway Economic Note N. 1. 'Valuation of Benefits of Prevention of Road Accidents and Casualties'. Department for Transport.

DfT. 2010. Department for Transport. *Vehicles Factsheet*. Department for Transport, London. pp. 4. Available for download at <http://www.dft.gov.uk/statistics>

Forest Research. 2010. *Benefits of green infrastructure - Report by Forest Research*. Forest Research, Farnham, Surrey. 42 pp.

HSE. 1996. *Use of Risk Assessment Within Government Departments*. Report prepared by the Interdepartmental Liaison Group on Risk Assessment. Health and Safety Executive. HSE Books, Sudbury, Suffolk. 48 pp.

HSE. 2001. *Reducing Risks: Protecting People*. Health and Safety Executive, [online]. Available for download at <http://www.hse.gov.uk/risk/theory/r2p2.pdf> (accessed 05/11/2013).

HSE. 2013. *Sector Information Minute - Management of the risk from falling trees or branches*. Health & Safety Executive, Bootle, [online]. Available for download at http://www.hse.gov.uk/foi/internalops/sims/ag_food/010705.htm (accessed 05/11/2013).

ISO. 2009. ISO Guide 73. *Risk Management Vocabulary*. International Organization for Standardization. Geneva. 17 pp.

Tritton, L. M. and Hornbeck, J. W. 1982. *Biomass Equations for Major Tree Species*. General Technical Report NE69. United States Department of Agriculture.

Revision 5.1.5. Monetary values for non-uk versions updated at 1st January 2016.

© 2016. Published by Quantified Tree Risk Assessment Limited. 9 Lowe Street, Macclesfield, Cheshire, SK11 7NJ, United Kingdom.