

Figure E.23 Peak levels at cross section CS25




Figure E.24 Peak levels at cross section CS26






Figure E.25 Peak levels at cross section CS27




Figure E.26 Peak levels at cross section CS28






Figure E.27 Peak levels at cross section CS29




Figure E.28 Peak levels at cross section CS30






Figure E.29 Peak levels at cross section CS31




Figure E.30 Peak levels at cross section CS32






Figure E.15 Long section CS01 to CS24




Figure E.15 Long section CS25 to CS32





APPENDIX F: ISIS OUTPUTS: PROPOSED SCENARIO SCHEMATIC,

LONG-SECTION AND CROSS-SECTIONS








Figure F.1 Peak levels at cross section CS01




Figure F.2 Peak levels at cross section CS02






Figure F.3 Peak levels at cross section CS03




Figure F.4 Peak levels at cross section CS04






Figure F.5 Peak levels at cross section CS05




Figure F.6 Peak levels at cross section CS06






Figure F.7 Peak levels at cross section CS07




Figure F.8 Peak levels at cross section CS08






Figure F.9 Peak levels at cross section CS09




Figure F.10 Peak levels at cross section CS101






Figure F.11 Peak levels at cross section CS11




Figure F.12 Peak levels at cross section CS14






Figure F.13 Peak levels at cross section CS15




Figure F.14 Peak levels at cross section CS16






Figure F.15 Peak levels at cross section CS17




Figure F.16 Peak levels at cross section CS18






Figure F.17 Peak levels at cross section CS19




Figure F.18 Peak levels at cross section CS20






Figure F.19 Peak levels at cross section CS21




Figure F.20 Peak levels at cross section CS22






Figure F.21 Peak levels at cross section CS23




Figure F.22 Peak levels at cross section CS24






Figure F.23 Peak levels at cross section CS25




Figure F.24 Peak levels at cross section CS26






Figure F.25 Peak levels at cross section CS27




Figure F.26 Peak levels at cross section CS28






Figure F.27 Peak levels at cross section CS29




Figure F.28 Peak levels at cross section CS30






Figure F.29 Peak levels at cross section CS31




Figure F.30 Peak levels at cross section CS32






Figure F.31 Long section CS01 to CS24






Figure F.32 Long section CS25 to CS32





APPENDIX G: FLOOD MODELLER OUTPUTS: SENSITIVITY TESTING





| Cross section | 1% AEP level (mAOD) | Manning's roughness n+20% (mAOD) | Difference (m) | Manning's roughness n-20% (mAOD) | Difference (m) | 1% AEP Flow + 20% level (mAOD) | Difference (m) |
|------------------|---------------------------|---|-------------------|---|-------------------|---|-------------------|
| CS01 | 116.064 | 116.095 | 0.031 | 116.033 | -0.031 | 116.095 | 0.031 |
| CS02 | 114.892 | 114.920 | 0.028 | 114.858 | -0.034 | 114.920 | 0.028 |
| CS03 | 113.506 | 113.530 | 0.024 | 113.471 | -0.035 | 113.528 | 0.022 |
| CS04 | 112.883 | 112.884 | 0.001 | 112.883 | 0.000 | 112.917 | 0.034 |
| CS05 | 111.444 | 111.478 | 0.034 | 111.421 | -0.023 | 111.474 | 0.030 |
| CS06 | 109.972 | 109.996 | 0.024 | 109.942 | -0.030 | 110.001 | 0.029 |
| CS07 | 109.077 | 109.080 | 0.003 | 109.069 | -0.008 | 109.400 | 0.323 |
| CS08 | 107.949 | 107.980 | 0.031 | 107.919 | -0.030 | 107.973 | 0.024 |
| CS09 | 107.590 | 107.591 | 0.001 | 107.589 | -0.001 | 107.621 | 0.031 |
| CS10 | 106.966 | 106.989 | 0.023 | 106.935 | -0.031 | 106.985 | 0.019 |
| CS11 | 106.487 | 106.487 | 0.000 | 106.485 | -0.002 | 106.509 | 0.022 |
| CS14 | 106.154 | 106.158 | 0.004 | 106.152 | -0.002 | 106.229 | 0.075 |
| CS15 | 106.152 | 106.155 | 0.003 | 106.150 | -0.002 | 106.228 | 0.076 |
| CS16 | 105.222 | 105.249 | 0.027 | 105.195 | -0.027 | 105.249 | 0.027 |
| CS17 | 103.936 | 103.947 | 0.011 | 103.925 | -0.011 | 103.947 | 0.011 |
| CS18 | 103.496 | 103.524 | 0.028 | 103.467 | -0.029 | 103.523 | 0.027 |
| CS19 | 103.496 | 103.524 | 0.028 | 103.467 | -0.029 | 103.523 | 0.027 |
| CS20 | 102.933 | 102.974 | 0.041 | 102.893 | -0.040 | 103.143 | 0.210 |
| CS21 | 102.837 | 102.877 | 0.040 | 102.833 | -0.004 | 103.137 | 0.300 |
| CS22 | 102.827 | 102.866 | 0.039 | 102.829 | 0.002 | 103.136 | 0.309 |
| CS23 | 101.440 | 101.468 | 0.028 | 101.405 | -0.035 | 101.450 | 0.010 |
| CS24 | 101.352 | 101.389 | 0.037 | 101.304 | -0.048 | 101.361 | 0.009 |
| CS25 | 106.028 | 106.052 | 0.024 | 106.000 | -0.028 | 106.125 | 0.097 |
| CS26 | 105.911 | 105.911 | 0.000 | 105.911 | 0.000 | 106.059 | 0.148 |
| CS27 | 105.274 | 105.288 | 0.014 | 105.267 | -0.007 | 105.309 | 0.035 |
| CS28 | 104.893 | 104.929 | 0.036 | 104.852 | -0.041 | 104.917 | 0.024 |
| CS29 | 104.336 | 104.358 | 0.022 | 104.312 | -0.024 | 104.399 | 0.063 |
| CS30 | 104.274 | 104.275 | 0.001 | 104.274 | 0.000 | 104.352 | 0.078 |
| CS31 | 103.806 | 103.849 | 0.043 | 103.749 | -0.057 | 103.851 | 0.045 |
| CS32 | 103.496 | 103.524 | 0.028 | 103.467 | -0.029 | 103.523 | 0.027 |
| Maximum | | | 0.043 | | -0.057 | | 0.323 |
| Mean | | | 0.022 | | -0.021 | | 0.073 |

Table G.1 Sensitivity analysis on 1 in 100 year peak water level





APPENDIX H: NOTES OF LIMITATIONS

The data essentially comprised a study of available documented information from various sources together with discussions with relevant authorities and other interested parties. There may also be circumstances at the site that are not documented. The information reviewed is not exhaustive and has been accepted in good faith as providing representative and true data pertaining to site conditions. If additional information becomes available which might impact our l conclusions, we request the opportunity to review the information, reassess the potential concerns and modify our opinion if warranted.

It should be noted that any risks identified in this report are perceived risks based on the available information.

This report was prepared by Betts Hydro Ltd for the sole and exclusive use of the titled client in response to particular instructions. Any other parties using the information contained in this report do so at their own risk and any duty of care to those parties is excluded.

This document has been prepared for the titled project only and should any third party wish to use or rely upon the contents of the report, written approval from Betts Associates Ltd must be sought.

Betts Associates Ltd accepts no responsibility or liability for the consequences of this document being used for the purpose other than that for which it was commissioned and for this document to any other party other than the person by whom it was commissioned.



APPENDIX I: PFRA/SFRA PLANNING EXTRACTS

Lancashire PFRA Locally Agreed Surface Water Information







Figure 5.2 - Locally Agreed Surface Water Information



MAP 1 RIBBLE VALLEY STRATEGIC FLOOD RISK ASSESSMENT

Scale: 1:115000 This map is reproduced from Ordnance Survey material with the permission of Ordnance Survey on behalf of the Controller of Her Majesy's Stationery Office © Crown copyright. Unauthorised reproduction infringes Crown copyright and may lead to prosecution or civil proceedings.

Ribble Valley Borough Council. Licence 100018641 23 April 2009

Land off Chipping Lane, Longridge Flood Risk Assessment and Drainage Management Strategy



This page has been intentionally left blank



APPENDIX J: SURFACE WATER RUN-OFF CALCULATIONS



Greenfield runoff estimation for sites

www.uksuds.com | Greenfield runoff tool

Calculated by: Megan Berry

Site name: CHIPPINGS LANE

Site location: LONGRIDGE

This is an estimation of the greenfield runoff rate limits that are needed to meet normal best practice criteria in line with Environment Agency guidance "Preliminary rainfall runoff management for developments", W5-074/A/TR1/1 rev. E (2012) and the SuDS Manual, C753 (Ciria, 2015). This information on greenfield runoff rates may be the basis for setting consents for the drainage of surface water runoff from sites.

Site coordinates

Latitude: 53.83699° N

Longitude: 2.60329° W

Reference: 6489164

Date: 2018-11-07T12:58:15

| Methodology | FEH Statistical |
|-------------|-----------------|
|-------------|-----------------|

Site characteristics

| Total site area (ha) | 6.236 |
|----------------------|-------|
|----------------------|-------|

Methodology

| Qmed estimation method | Calculate from BFI and SAAR |
|----------------------------------|-----------------------------|
| BFI and SPR estimation method | Specify BFI manually |
| HOST class | 14 |
| BFI / BFIHOST | 0.377 |
| Qmed (I/s) | 78.38 |
| Qbar / Qmed Conversion Factor | 1.08 |

| Hydrological characteristics | Default | Edited |
|-------------------------------|---------|--------|
| SAAR (mm) | 1211 | 1211 |
| Hydrological region | 10 | 10 |
| Growth curve factor: 1 year | 0.87 | 0.87 |
| Growth curve factor: 30 year | 1.7 | 1.7 |
| Growth curve factor: 100 year | 2.08 | 2.08 |

Notes:

| 11000. |
|---------------------------------------|
| (1) Is Q _{BAR} < 2.0 I/s/ha? |
| |
| |
| |
| (2) Are flow rates < 5.0 l/s? |
| |
| |
| |
| |
| (3) Is SPR/SPRHOST ≤ 0.3? |
| |
| |
| |
| |

| Greenfield runoff rates | Default | Edited |
|-------------------------|---------|--------|
| Qbar (I/s) | 84.26 | 84.85 |
| 1 in 1 year (l/s) | 73.31 | 73.82 |
| 1 in 30 years (l/s) | 143.24 | 144.25 |
| 1 in 100 years (l/s) | 175.26 | 176.49 |

SURFACE WATER RUN-OFF CALCULATION SHEET

| Development | CHIPPINGS LANE, LONGRIDGE |
|-------------|---------------------------|
| Project No. | HYD371 |





| Areas | Catchment | Catchment Charateristics | | |
|--|-----------|--------------------------|------------------|-------------------------|
| Total Site | 10.659 | ha | SAAR | 1219 <mark>mm</mark> |
| Development Area (for SW Strategy) | 6.236 | ha | BFI | 0.377 |
| Existing Impermeable | 0.000 | ha | i ₁ | 19.3 <mark>mm/hr</mark> |
| Existing Impermeable (for SW Strategy) | 0.000 | ha | i ₃₀ | 37.4 <mark>mm/hr</mark> |
| Existing Pervious | 10.659 | ha | i ₁₀₀ | 48.2 <mark>mm/hr</mark> |
| Existing Pervious (for SW Strategy) | 6.236 | ha | | |
| Proposed Impermeable (total) | 2.806 | ha | | |
| Proposed Impermeable (domestic only) | 2.806 | ha | | |

| Run-off Rates | | | Volumes | | |
|---------------------|---------------|-----------|-----------------|--------|-------------|
| Pre-development | | | Pre-development | | |
| Impermeable | 1yr | 0.0 l/s | Impermeable | 1yr | 0.0 cu.m |
| | 30yr | 0.0 I/s | | 100yr_ | 0.0 cu.m |
| | 100yr | 0.0 l/s | Pervious | 1yr | 710.7 cu.m |
| | 50mm/hr | 0.0 l/s | | 100yr | 2178.7 cu.m |
| Pervious | 1yr | 73.8 l/s | Total | 1yr | 710.7 cu.m |
| | 30yr | 144.3 l/s | | 100yr | 2178.7 cu.m |
| | 100yr | 176.5 l/s | | | |
| | QBar | 84.9 l/s | | | |
| Total | 1yr | 73.8 l/s | | | |
| | 30yr | 144.3 l/s | | | |
| | 100y r | 176.5 l/s | | | |
| Post-development | | | | | |
| Impermeable (total) | 1yr | 150.2 l/s | | | |
| | 30yr | 291.3 l/s | | | |
| | 100yr+CC | 488.5 l/s | | | |
| | | | | | |
| | | | | | |
| | | | | | |

| Quick storage Estin | nates | | | | | | | | |
|---------------------|----------|------|------|------|----------------|---|----------------------|----------|-----|
| | | low | high | mean | Imp. Area (ha) | _ | Max. Discharge (I/s) | Rainfall | CC |
| Return Period | 1yr | 117 | 290 | 204 | 2.806 | | 84.9 | FEH | 0 |
| Return Period | 30yr | 515 | 853 | 684 | 2.806 | | 84.9 | FEH | 0 |
| Return Period | 100yr+CC | 989 | 1549 | 1269 | 2.806 | | 84.9 | FEH | 20% |
| Return Period | 100yr+CC | 1113 | 1720 | 1417 | 2.806 | | 84.9 | FEH | 30% |
| Return Period | 100yr+CC | 1240 | 1892 | 1566 | 2.806 | | 84.9 | FEH | 40% |

| Betts Associates Ltd | Page 1 | |
|----------------------------|----------------|----------|
| Old Marsh Farm Barns | CHIPPINGS LANE | |
| Welsh Road | LONGRIDGE | Care and |
| Sealand Flintshire CH5 2LY | | Micro |
| Date 07/11/2018 | Designed by MB | Drainage |
| File | Checked by DK | niamade |
| Micro Drainage | Network 2018.1 | |

Rainfall profile

Storm duration (mins) 360

FEH Data

FEH Rainfall Version 2013

Site Location GB 360097 438896

Data Type Point

Peak Intensity (mm/hr) 48.210

Ave. Intensity (mm/hr) 12.298

Return Period (years) 100.0

