

Safety, Health & Environmental Information: In addition to the hazards and risks normally associated with the types of work detailed on this drawing, please



note the significant hazards identified by symbols below, INDICATES A RESIDUAL RISK AS A WARNING



and described below:

Construction/Maintenance/Cleaning/Demolition Refer to Drawing:

General Notes:

1. Do not scale from this drawing.

2. All dimensions are in millimetres (mm), all levels in metres (m) unless noted otherwise.

3. Discrepancies or omissions are to be reported to the Engineer prior to work commencing.

4. Materials and workmanship are to comply in all respects with current British Standard Specifications, Codes of Practice, and Building Regulations Approved Documents.

5. The copyright of this drawing is vested in the Engineer and must not be copied or reproduced without written consent.

6. The Contractor is to check and verify all building and site dimensions, levels and sewer invert levels at connection points before work commences.

7. This drawing is to be read in conjunction with all relevant specifications and drawings issued by the Engineer, Architect and other Specialists.

Notes:

- 1. The contractor is to check all information provided prior to commencing works, and seek clarification from the engineer in respect to any ambiguities found.
- 2. Contractor to check insitu CBR at time of construction and adjust pavement foundation as per Table 3. Assumed Site CBR 3% <= CBR < 5%
- 3. Contractor to check that the existing subgrade is not frost-susceptible. If found to be frost-susceptible, contractor to ensure all material within 450mm depth from the pavement surface is non frost-susceptible by adding a capping layer below the sub-base.

Table 3: Class 2 Pavement Foundation Options	
In-situ CBR	Type 1 sub base to DfT SHW Clause 803
7% - 20%	100
5% - 7%	150
3% - 5%	250
2% - 3%	325
< 2%	Consult Engineer for Advice

