

Specifications Table for 4MXM-A9

					4MXM68A2V1B9	4MXM80A2V1B9	
Dimensions	Unit		Height	mm	734	734	
			Width	mm	974	974	
			Depth	mm	408	408	
Weight	Unit			kg	63	67	
Compressor	Type				Hermetically sealed swing compressor	Hermetically sealed swing compressor	
Operation range	Cooling	Ambient	Min.	°CDB	-10	-10	
			Max.	°CDB	46	46	
Sound pressure level	Cooling		Nom.	dBA	48	48	
	Heating		Nom.	dBA	49	49	
Refrigerant	Type				R-32	R-32	
	Charge				kg	2	2.4
	Charge				tCO2Eq	1.35	1.62
	GWP					675	675
Piping connections	Piping length	OU - IU	Max.	m	25 (1)	25 (1)	
			Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 30m)

Give Feedback

	Level difference	IU - OU	Max.	m	15	15
		IU - IU	Max.	m	7.5	7.5
	Total piping length	System	Actual	m	60	70
Standard Accessories	Installation manual				1	1
	Drain cap				3	3
	Drain plug				1	1
	Reducer assembly				1	1
	Screw bag				1	1
Power supply	Phase				1~	1~
	Frequency			Hz	50	50
	Voltage			V	220-240	220-240
Notes					(1) - For one room	(1) - For one room

