

SHD2741-SHD-HLG-ACCR-SH-EO-Lighting Schedule-R0

Proposed Unit No.	Easting Coordinates	Northing Coordinates	Unit Location	Unit Description	Service Connection Type	Primary Isolator	Secondary Isolator	Private Cable Network Termination Type
FP01	373538.4910	436101.5912	Refer to 'SHD2741-SHD-HLG-ACCR-DR-EO-Lighting Layout-R0' Private street lighting layout drawing	Proposed stainless steel feeder pillar finished in factory applied powder coated black (RAL 9005) finish, incorporating IDNO electrical supply connection with electric meter (Model: Ritherdon RH400 or equivalent specification with 6 way distribution board with 100A main switch and BS 88 outgoing fuses)	Proposed IDNO supply with secondary isolation	IDNO approved double pole isolator including electrical Kwh meter	4 way distribution board with 100A main switch and BS 88 type 2 outgoing fuses including electrical Kwh meter	Termination Type T3
PR01	373538.0109	436094.7611	Refer to 'SHD2741-SHD-HLG-ACCR-DR-EO-Lighting Layout-R0' Private street lighting layout drawing	Galvanised tubular steel lighting column of 6.0 metre nominal height and planted base with glass flake root protection, as supplied by Fabrikat, in factory applied black (RAL 9005) finish, complete with post top mounted at 0° tilt, Urbis Axia 3.2 5293 300mA 478962 rear louvers neutral white 2.75klm 22w LED luminaire (RAL 9005) & Lucy Zodion Hawk3 10lux (1:1) PECU mounted in 7pin NEMA socket.	Private cable network connection	32A double pole isolator and BS 88 type 2 outgoing fuse to luminaire	N/A	Termination Type T2
PR02	373517.3179	436102.0511	Refer to 'SHD2741-SHD-HLG-ACCR-DR-EO-Lighting Layout-R0' Private street lighting layout drawing	Galvanised tubular steel lighting column of 6.0 metre nominal height and planted base with glass flake root protection, as supplied by Fabrikat, in factory applied black (RAL 9005) finish, complete with post top mounted at 0° tilt, Urbis Axia 3.2 5293 300mA 478962 rear louvers neutral white 2.75klm 22w LED luminaire (RAL 9005) & Lucy Zodion Hawk3 10lux (1:1) PECU mounted in 7pin NEMA socket.	Private cable network connection	32A double pole isolator and BS 88 type 2 outgoing fuse to luminaire	N/A	Termination Type T1
PR03	373512.1542	436080.1052	Refer to 'SHD2741-SHD-HLG-ACCR-DR-EO-Lighting Layout-R0' Private street lighting layout drawing	Galvanised tubular steel lighting column of 6.0 metre nominal height and planted base with glass flake root protection, as supplied by Fabrikat, in factory applied black (RAL 9005) finish, complete with post top mounted at 0° tilt, Urbis Axia 3.2 5293 300mA 478962 rear louvers neutral white 2.75klm 22w LED luminaire (RAL 9005) & Lucy Zodion Hawk3 10lux (1:1) PECU mounted in 7pin NEMA socket.	Private cable network connection	32A double pole isolator and BS 88 type 2 outgoing fuse to luminaire	N/A	Termination Type T1