

Edisford Playing Pitches

3G Pitch

Date: 13-07-2026

Designer: Andy Poplett

Description:

The nominal values shown in this report are the result of precision calculations, based upon precisely positioned luminaires in a fixed relationship to each other and to the area under examination. In practice the values may vary due to tolerances on luminaires, luminaire positioning, reflection properties and electrical supply.

Signify

Unit 3

Guildford Business Park

Guildford

Surrey

GU2 8XG

Mobile Phone: 0044 7810 832266

E-Mail: andrew.poplett@signify.com

Table of Contents

1.	Project Description	3
1.1	Description	3
1.2	Top Project Overview	4
2.	Summary	5
2.1	Observer Information	5
2.2	Project Luminaires	5
2.3	Calculation Results	5
3.	Calculation Results	7
3.1	Football: Graphical Table	7
3.2	Half Pitch: Graphical Table	8
3.3	Spillage: Graphical Table	9
3.4	Spillage: Iso Contour	10
3.5	Spillage: Filled Iso Contour	11
3.6	Ev Grid 1: Graphical Table	12
3.7	Ev Grid 2: Graphical Table	13
4.	Luminaire Details	14
4.1	Project Luminaires	14

1. Project Description

1.1 Description

Maintenance Factor:- 0.90

Pitch 91m x 55m (Fenced Area 97m x 61m)

The design has been completed using the Philips Asymmetric OptiVision LED GEN 3.5 A35 Floodlights. A total of 12 no have been used to achieve an average of 200lux.

Floodlights are mounted on 6 x 15 metre columns

All Floodlights fitted with integral LO (maximum cut off) louvres to reduce spill and glare.

1.2 Top Project Overview



Scale
1:1250

2. Summary

2.1 Observer Information

Code	Observer	Position		
		X (m)	Y (m)	Z (m)
Aa	49 Blakewater Rd	-44.70	-105.20	1.50
Bb	51 Blakewater Rd	-50.70	-93.90	1.50
Cc	53 Blakewater Rd	-54.60	-86.90	1.50
Dd	55 Blakewater Rd	-60.30	-76.60	1.50
Ee	57 Blakewater Rd	-64.90	-67.30	1.50
Ff	59 Blakewater Rd	-69.20	-59.40	1.50
Gg	61 Blakewater Rd	-72.90	-51.10	1.50
Hh	63 Blakewater Rd	-78.90	-40.80	1.50
Ii	42 Ribble Prospect	-82.40	-24.90	1.50

2.2 Project Luminaires

Code	Qty	Luminaire Type	Lamp Type	Power (W)	Flux (lm)
N	8	BVP528 OUT T35 A35-NB LO	1 * LED2590-4S/757	1505.9	1 * 259000
O	4	BVP528 OUT T35 A35-NMB LO	1 * LED2590-4S/757	1505.9	1 * 259000

The total installed power: 18.07 (kWatt)

Number of Luminaires Per Switching Mode:

Switching Mode	Luminaire Code		Power (kWatt)
	N	O	
Main Pitch	8	4	18.07
Half Pitch	4	2	9.04
All ON	8	4	18.07

Number of Luminaires Per Arrangement:

Arrangement	Luminaire Code		Power (kWatt)
	N	O	
Centre 1	0	2	3.01
Centre 2	0	2	3.01
Corner 1	4	0	6.02
Corner 2	4	0	6.02

2.3 Calculation Results

Switching Modes:

Code	Switching Mode	Maintenance factor
1	Main Pitch	0.90
2	Half Pitch	0.90
3	All ON	1.00

(II)luminance Calculations:

Calculation	Switching Mode	Type	Unit	Ave	Max	Min/Ave	Min/Max
Football	1	Surface Illuminance	lux	233		0.69	0.51
Half Pitch	2	Surface Illuminance	lux	209		0.61	0.42
Spillage	3	Surface Illuminance	lux	43.1		0.00	0.00
Ev Grid 1	3	Surface Illuminance	lux		0.23		
Ev Grid 2	3	Surface Illuminance	lux		0.07		

Obtrusive Light Calculations:

Switching Mode	Observer Code	Luminaire Code	Position			Aiming Angles			Maximum Intensity (cd)
			X (m)	Y (m)	Z (m)	Rot.	Tilt90	Tilt0	
1	Aa	O	1.60	32.50	15.00	-120.00	69.00	-0.00	888
1	Bb	O	1.60	32.50	15.00	-120.00	69.00	-0.00	878
1	Cc	O	1.60	32.50	15.00	-120.00	69.00	-0.00	904
1	Dd	O	1.60	32.50	15.00	-120.00	69.00	-0.00	915
1	Ee	O	1.60	32.50	15.00	-120.00	69.00	-0.00	940
1	Ff	O	1.60	32.50	15.00	-120.00	69.00	-0.00	927
1	Gg	O	1.60	32.50	15.00	-120.00	69.00	-0.00	965
1	Hh	O	1.60	32.50	15.00	-120.00	69.00	-0.00	955
1	Ii	O	1.60	32.50	15.00	-120.00	69.00	-0.00	1137


Switching Mode	ULR
1	0.00
2	0.00
3	0.00

3. Calculation Results

3.1 Football: Graphical Table

Main Pitch

Grid : Football at Z = -0.00 m
 Calculation : Surface Illuminance (lux)



N BVP528 OUT T35 A35-NB LO BVP528 OUT T35 A35-NMB L

Average
233

Min/Ave
0.69

Min/Max
0.51


Project maintenance factor
0.90

Scale
1:750

3.2 Half Pitch: Graphical Table

Half Pitch

Grid : Half Pitch at Z = -0.00 m
Calculation : Surface Illuminance (lux)




Average	Min/Ave	Min/Max	Project maintenance factor	Scale
209	0.61	0.42	0.90	1:400

3.3 Spillage: Graphical Table

All ON

Grid : Spillage at Z = -0.00 m
 Calculation : Surface Illuminance (lux)



N BVP528 OUT T35 A35-NB LO BVP528 OUT T35 A35-NMB L

Average
43.1

Min/Ave
0.00

Min/Max
0.00

Project maintenance factor
1.00

Scale
1:1250

3.4 Spillage: Iso Contour


All ON

Grid

Calculation

: Spillage at Z = -0.00 m

: Surface Illuminance (lux)



Average43.1

Min/Ave0.00

Min/Max0.00

Project maintenance factor1.00

Scale1:1250

3.5 Spillage: Filled Iso Contour



All ON

Grid

Calculation

: Spillage at Z = -0.00 m

: Surface Illuminance (lux)



N

BVP528 OUT T35 A35-NB LO

O

BVP528 OUT T35 A35-NMB L

Average
43.1

Min/Ave
0.00

Min/Max
0.00

Project maintenance factor
1.00

Scale
1:2000

3.7 Ev Grid 2: Graphical Table


All ON

Grid

: Ev Grid 2

Calculation

: Surface Illuminance (lux)



(-99.60, -33.60, 5.00) C-----D (-80.20, -23.30, 5.00)

(-99.60, -33.60, 1.00) A-----B (-80.20, -23.30, 1.00)

N : BVP528 OUT T35 A35-NB LO

O : BVP528 OUT T35 A35-NMB LO

Maximum

0.07

Project maintenance factor

1.00

Scale

1:150

4. Luminaire Details

4.1 Project Luminaires

OptiVision LED gen3.5 2022

BVP528 OUT T35 1xLED2590-4S/757/757 E3/D4I A35-NB LO

Light output ratios

DLOR : 0.59

ULOR : 0.00

TLOR : 0.59


Ballast : E3/D4I

Lamp flux : 259000 lm

Luminaire wattage : 1505.9 W

Measurement code : LVM2047300

Note: Luminaire data not from database.



OptiVision LED gen3.5 2022

BVP528 OUT T35 1xLED2590-4S/757/757 E3/D4I A35-NMB LO

Light output ratios

DLOR : 0.58

ULOR : 0.00

TLOR : 0.58

Ballast : E3/D4I

Lamp flux : 259000 lm

Luminaire wattage : 1505.9 W

Measurement code : LVM2L47600

Note: Luminaire data not from database.

